


- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ POSTS:  
 GOLD FLASH OVER  
 PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES,  
 .000100 MIN TIN-LEAD PLATE ON THE SOLDER-TAIL,  
 .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE POST.  
 OR  
 .000030 MIN GOLD PLATE ON THE MATING SURFACES,  
 .000100 MIN TIN-LEAD PLATE ON THE SOLDER-TAIL,  
 .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- △ DOUBLE BAR POLARIZATION
- △ CENTER POLARIZATION SLOT
- △ FOR 10 POSN ASSEMBLY, SLOT OMITTED WHERE INDICATED
- △ OPTIONAL AMP IDENTIFICATION NUMBER (DATE CODE).  
 LOCATION APPROXIMATELY WHERE SHOWN.
- △ NUMBER 1 POSITION.
- △ HOUSING: GLASS FILLED NYLON, FLAME RETARDENT, BLACK.
- △ POSTS: BRASS



OBSOLETE	1.800	1.400	14	30	1-104313-2
OBSOLETE	3.300	2.900	29	60	1-104313-0
OBSOLETE	2.800	2.400	24	50	104313-9
OBSOLETE	2.500	2.100	21	44	104313-8
	2.300	1.900	19	40	104313-7
	2.000	1.600	16	34	104313-5
	1.600	1.200	12	26	104313-5
	1.300	.900	9	20	104313-4
	1.100	.700	7	16	104313-3
	1.000	.600	6	14	104313-2
	.800	.400	4	10	104313-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	DATE	BY	CHK	APP
WORKS		1				
DESIGNED BY		108-40018	TE Connectivity			
PROJECT FILE		108-40018	TE Connectivity			
DATE		DATE	DATE	DATE	DATE	DATE
CUSTOMER DRAWING		A1	00779	G=104313	REVISED TO	