



MOLEX IRELAND PRODUCTION ONLY
(OPTION)

RECOMMENDED PCB HOLE LAYOUT

NOTES:

1. PIN PUSH-OUT FORCE (.9072KG)/2LBS MIN.
 2. PIN SOLDERABILITY PER MOLEX SPEC. ES-152.
 3. PRODUCT SPEC: PS-70246 APPLIES.
 4. WAFER TO BE FLAT WITHIN .003 MM/MM.
 5. DIMENSIONS FOR PLATING LOCATION:
- △A MEASURE POINT FOR THICKNESS
 - △SB MINIMUM COVERAGE
 - △6. GOLD END OF PIN UNLESS OVERALL PLATED.

- 573 : 20 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 100 MICRO INCHES MIN TIN PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 573A : 20 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 100 MICRO INCHES MIN TIN/LEAD PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.

△8. DIM AT THE CENTRE OF THE SHROUDED WALL SHALL BE 5.91MM MIN. THIS SPEC IS VALID FOR ALL CKT SIZE.

9. MATERIAL:
HSG: PBT, UL94V-0, COLOUR BLACK
PIN: 0.64MM SQ. PIN PHOSPHOR BRONZE.

△7. FINISH:

- 571 : 15 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 571A: 15 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN/LEAD PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 574 : 30 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 574A: 30 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN/LEAD PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 544 : 5 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.
- 544A: 5 MICRO INCHES MIN GOLD PLATE ON CONTACT AND 75 MICRO INCHES MIN TIN/LEAD PLATE ON SOLDERTAIL BOTH OVER 50 MICRO INCHES MIN NICKEL OVERALL.

UPDATE REVISION EC NO. S2006-0664 2006/02/07 DRAWN BY: J1A0 CHECKED BY: CHICK BROWN APPROVED BY: JPLI 2006/02/13	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		mm INCH	DRAWN BY JENNIFER 1987/09/18	DATE 1987/09/18	TITLE C-GRID, SHROUDED HEADER (SLOTTED W/O STANDOFFS)			
J3 REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE TABLE		MATERIAL NO. ALANB 1987/09/18		MOLEX INCORPORATED		
		SIZE A3		DOCUMENT NO. SDA-70246-**-20-25,39-41		SHEET NO. 1 OF 2		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								

10 9 8 7 6 5 4 3 2 1

PART NUMBER	CKT SIZE	VOID CKT	DIM A	DIM B	DIM C	DIM D
70246-08**	08	-	7.62	14.73	17.78	15.24
70246-10**	10	-	10.16	17.27	20.32	17.78
70246-12**	12	-	12.70	19.81	22.86	20.32
70246-14**	14	-	15.24	22.35	25.40	22.86
70246-16**	16	-	17.78	24.89	27.94	25.40
70246-20**	20	-	22.86	29.97	33.02	30.48
70246-24**	24	-	27.94	35.05	38.10	35.56
70246-26**	26	-	30.48	37.59	40.64	38.10
70246-30**	30	-	35.56	42.67	45.72	43.18
70246-34**	34	-	40.64	47.75	50.80	48.26
70246-40**	40	-	48.26	55.37	58.42	55.88
70246-44**	44	-	53.34	60.45	63.50	60.96
70246-50**	50	-	60.96	68.07	71.12	68.58
70246-56**	56	-	68.58	75.69	78.74	76.20
70246-60**	60	-	73.66	80.77	83.82	81.28
70246-64**	64	-	78.74	85.85	88.90	86.36
70246-72**	72	-	88.90	96.01	99.06	96.52
70246-25**	26	26	30.48	37.59	40.64	38.10

LEGEND:
 A-70246 - * * * *
 CKT SIZE
 PLATING OPT.
 SEE TABLE FOR DETAIL

△ PART NUMBER	PLATING OPTION (TIN/LEAD)	△ PART NUMBER	PLATING OPTION (TIN)
70246-**21	571A	70246-**01	571
70246-**22	574A	70246-**02	574
70246-**24	544A	70246-**04	544
70246-**20	573A	70246-**12	573

C

B

A

ADD PART NUMBER EC NO. S2006-0664 DRAWN BY: J1A0 CHECKED BY: CHIKO-BONOK APPROVED BY: PTLIM 2006/02/07 2006/02/07 2006/02/13	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr><td>4 PLACES</td><td>± .005</td><td>± .0001</td></tr> <tr><td>3 PLACES</td><td>± .005</td><td>± .0001</td></tr> <tr><td>2 PLACES</td><td>± 0.20</td><td>± .008</td></tr> <tr><td>1 PLACE</td><td>± .005</td><td>± .0001</td></tr> <tr><td colspan="3">ANGULAR ± 3 °</td></tr> </tbody> </table>		mm	INCH	4 PLACES	± .005	± .0001	3 PLACES	± .005	± .0001	2 PLACES	± 0.20	± .008	1 PLACE	± .005	± .0001	ANGULAR ± 3 °			DIMENSION STYLE MM ONLY DRAWN BY: JENNIFER DATE: 1987/09/18 CHECKED BY: RWONG DATE: 1987/09/18 APPROVED BY: ALANB DATE: 1987/09/18	SCALE: NTS DESIGN UNITS: METRIC THIRD ANGLE PROJECTION	TITLE: C-GRID, SHROUDED HEADER (SLOTTED W/O STANDOFFS)
		mm	INCH																				
	4 PLACES	± .005	± .0001																				
	3 PLACES	± .005	± .0001																				
2 PLACES	± 0.20	± .008																					
1 PLACE	± .005	± .0001																					
ANGULAR ± 3 °																							
MATERIAL NO. SEE TABLE SIZE: A3	DOCUMENT NO. SDA-70246-**20-25,39-41 SHEET NO. 2 OF 2	MOLEX INCORPORATED THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS																							

10 9 8 7 6 5 4 3 2 1

ib_frame_A3_P_ME_1
 Rev. D 2004/04/02