

## Features

- DC to 5 GHz
- Terminal for lead attachment
- Low VSWR
- Aluminum Nitride substrate

## Applications

- Drop-In isolators
- Hybrid couplers
- RF power amplifiers

# CHF3523xNT Series Power RF Chip Termination

### General Specifications


Substrate.....ALN  
 Resistor.....Thick Film  
 Resistance.....50 Ω  
 Tolerance.....±5 %  
 Packaging.....100 pcs./bag

### Absolute Ratings


Power  
 Version C.....150 W  
 Version D.....100 W  
 Frequency  
 Version C.....3 GHz  
 Version D.....5 GHz  
 VSWR\*  
 Version C.....1.2 Maximum  
 Version D.....1.1 Maximum

\*VSWR <1.06 for Frequency <3.5 GHz.

### Derating Curve



### Product Dimensions



DIMENSIONS =  $\frac{\text{MILLIMETERS}}{\text{(INCHES)}}$

### How To Order

CHF 3523 x N T 500 L W

Model \_\_\_\_\_  
 Size \_\_\_\_\_  
 Version \_\_\_\_\_  
 C = 150 W, 3 GHz  
 D = 100 W, 5 GHz  
 Substrate \_\_\_\_\_  
 Mount \_\_\_\_\_  
 T = Tab  
 Value \_\_\_\_\_  
 500 = 50 Ohm  
 Function \_\_\_\_\_  
 L = Termination  
 Finish \_\_\_\_\_  
 W = Tin Plated



Reliable Electronic Solutions

**Asia-Pacific:**  
 Tel: +886-2 2562-4117  
 Fax: +886-2 2562-4116

**Europe:**  
 Tel: +41-41 768 5555  
 Fax: +41-41 768 5510

**The Americas:**  
 Tel: +1-951 781-5500  
 Fax: +1-951 781-5700

[www.bourns.com](http://www.bourns.com)

\*RoHS Directive 2002/95/EC Jan 27 2003, including Annex  
 Specifications are subject to change without notice.  
 Customers should verify actual device performance in their specific applications.