



MPD Series	Flange Recess	Clearance Hole	Recommended Flange Diameter	Typical Stimpson P/N
	0.180" wide x 0.040" deep	0.093"	0.150"	GS-3 Series, 0.089 O.D.

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
4/29/06	A	Added dimensions Updated notes	T.B.	B.S.	
4/26/08	B	Added dimension 0.51	T.B.	B.S.	



NOTES:

- MATERIAL:**
 HOUSING : BLACK POLYPROPYLENE, PP4410
 FLAMMABILITY RATING -UL94V-0, UL FILE NO. E107536
 TEMPERATURE RANGE: -20°C TO +110°C
 SPRING: STAINLESS STEEL, NICKLE PLATED
 TERMINAL: BRASS, NICKLE PLATED, FAST ON TABS OR SOLDER LUGS
- ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal $\pm .5$ (.020)	Scale	Drawn By B.S.	
Fractional $\pm .8$ (.030)	Title 6V BATTERY HOLDER		
Angular $\pm 3^\circ$	Date 4/26/08	Drawing Number BH223-L	
Approved By T.B.			