

# Spezifikation für Freigabe / specification for release


Kunde / customer : \_\_\_\_\_  
 Artikelnummer / part number : **7447462102**



Bezeichnung : **Tonneninduktivität WE-TI**  
 description : **Filter Choke WE-TI**

DATUM / DATE : 2010-02-22

## A Mechanische Abmessungen / dimensions:



	Typ "XS"	
A	<b>6,0 max.</b>	mm
B	<b>8,5 max.</b>	mm
C	<b>3,5 +1,0/-0,5</b>	mm
D	<b>2,0 max.</b>	mm
E	<b>2,5 ± 0,5</b>	mm
F	<b>∅ 0,5 ref</b>	mm

● = Start of winding      Marking = Inductance code

## B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Leerlauf-Induktivität / inductance	<b>1 kHz / 0,25V</b>	$L_0$	<b>1000,0</b>	$\mu\text{H}$	<b>±10%</b>
DC-Widerstand / DC-resistance	<b>@ 20° C</b>	$R_{DC \text{ max.}}$	<b>6,000</b>	$\Omega$	<b>max.</b>
Nennstrom / nominal current	<b><math>\Delta T = 40 \text{ K}</math></b>	$I_N$	<b>0,25</b>	A	<b>max.</b>
Sättigungsstrom / saturating current	<b><math> \Delta L / L_0  - 10\%</math></b>	$I_{\text{sat}}$	<b>0,27</b>	A	<b>typ.</b>

## D Prüfgeräte / test equipment:

**Wayne Kerr 3260B** für/for  $L_0$   
**GMC Metrahit 271 Milliohmmeter** für/for  $R_{DC}$   
**Fluke 54II Thermometer** für/for  $I_{DC}$

## E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%  
 Umgebungstemperatur / temperature: +20°C

## F Werkstoffe & Zulassungen / material & approvals

Basismaterial / base material: Ferrit/ferrite  
 Draht / wire: Class F  
 shrink tube: Polyoefine

## G Eigenschaften / general specifications:

Betriebstemp. / operating temperature: -40°C - + 125°C  
 Umgebungstemp. / ambient temperature: -40°C - + 85°C  
 It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:	<b>Kunde / customer</b>			
	Datum / date	Unterschrift / signature		
	<b>Würth Elektronik</b>			
	Geprüft / checked	Kontrolliert / approved	CZ	Version 1      10-02-22
			Name	Änderung / modification      Datum / date

### Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.com>

# Spezifikation für Freigabe / specification for release

Kunde / customer : \_\_\_\_\_


Artikelnummer / part number : **7447462102**



Bezeichnung : **Tonneninduktivität WE-TI**  
 description : **Filter Choke WE-TI**

DATUM / DATE : 2010-02-22

## H Induktivitätskurve / Inductance curve :



Freigabe erteilt / general release:	<b>Kunde / customer</b>			
.....	.....			
Datum / date	Unterschrift / signature			
	<b>Würth Elektronik</b>			
.....	.....			
Geprüft / checked	Kontrolliert / approved	CZ	Version 1	10-02-22
		Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

### Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.com>