




LED COLOR			
ROW 1	ROW 2	ROW 3	ROW 4
RED / GREEN	RED / GREEN	RED / GREEN	RED / GREEN

LED COLOR = RED / GREEN					
OPERATING CHARACTERISTICS AT 25°C AMBIENT					
CHARACTERISTICS	MIN	TYP	MAX	UNITS	TEST CONDITIONS
LUMINOUS INTENSITY	2.5/3.7	4.7/10.0		mc d	$I_f = 10 \text{ mA}$
FORWARD VOLTAGE		2.0/2.1	2.8	V	$I_f = 20 \text{ mA}$
REVERSE CURRENT			100	$\mu\text{A}$	$V_R = 5 \text{ V}$
PEAK WAVELENGTH		635/565		nm	
VIEWING ANGLE		60		Degree	
CAPACITANCE		20/35		pf	$V_r = 0, f = 1 \text{ MHz}$

REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
A	-----	NEW RELEASE	AV			



NOTES:

- LEADS TO FIT INTO HOLES SPACED AS PER HOLE PATTERN
- LEADS TO BE FREE OF DEFORMATION AFTER BENDING AND CUTTING
- PIN NUMBERS FOR REFERENCE ONLY - DO NOT EXIST ON PART
- LED LEAD DIMENSIONS SHOWN ARE MEASURED AT HOUSING EXIT
- LEAD THICKNESS = .020 SQ.
- PACKAGING =  
BLOCKS ARE PLACED IN CLEAR ANTISTATIC TRAY  
50 BLOCKS PER TRAY
- DIALIGHT PART NUMBER: 568-0016-813

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE 4:1	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES	C-16710	A
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE 4X4 CB1 ARRAY BLOCK	
FRACTIONS: ±1/64	MATERIAL	
DECIMALS (.XXX): ±.020	FINISH:	
DECIMALS (.XXXX): ±.015	FSCM 83330	
ANGLES: ±3°	Dialight 1913 ATLANTIC AVE. MANASQUAN, N. J. 08736	
	SHEET OF	FAMILY TABLE: