



# RFI Shield Fingers

## Grounding Spring Contacts

- ❖ SMT devices for use in shielding and grounding applications.
- ❖ For use on surface mount PCBs, in contact with metal shields or frames.
- ❖ Suitable for both wiping and sliding actions.
- ❖ Ideal for automated requirements, using standard placement equipment.

SPECIFICATION		2.5mm HIGH	
<p>❖ <b>Materials</b></p> <p>Material: Copper Alloy Finish: See order code</p> <p>❖ <b>Packaging</b></p> <p>Packaging format: Tape &amp; Reel or Loose Reel quantity: S1761, S1791: 2,000 S1741: 2,500</p>		<p>Recommended PC Board Pattern</p>	
3.5mm HIGH		4.0mm HIGH	
<p>Recommended PC Board Pattern</p>		<p>Recommended PC Board Pattern</p>	

### HOW TO ORDER

**S17 X 1 - XX R**

SERIES CODE	
4	2.5mm High
6	3.5mm High
9	4.0mm High

PACKAGING	
<b>R</b>	Tape and Reeled
<b>Blank</b>	Loose

FINISH	
<b>42</b>	Gold + Tin (S1761, S1791)
<b>46</b>	Tin (S1741)

[www.harwin.com](http://www.harwin.com)

All dimensions in mm.



**HARWIN**