

A

DP-Series Precision Dipole Antennas

Product Overview

TDK RF Solutions' Precision Dipole Antennas are half-wave, fixed length precision dipoles designed to generate traceable calibrated fields or to measure electric fields at their respective frequency. The DP-series antennas offer low gain and essentially perfect cross-polarization rejection, and are typically used as a reference or standard gain antenna, or as a polarization standard.

Dipole Test Sets The DP-Series Dipole Antennas are designed with operating frequencies matched the operating frequencies of common mobile radio devices, and are available in sets that correspond to communication systems used in Europe, North America, and Asia, including GSM, TDMA, PCS, Bluetooth, and others. Custom frequencies are available.

Applications

- Calibration
- Communications testing
- Antenna pattern measurements



TDK RF Solutions' Dipole Antennas are specifically designed as calibration reference sources for transmitting and receiving the optimum field strength within each antenna's respective frequency range.



Communications Applications		
Communication System	Frequency Range	Model
GSM - NMT	453 MHz – 458 MHz	DP-450
GSM - 900	880 MHz – 925 MHz	DP-900
GSM - 1800	1710 MHz – 1785 MHz	DP-1800
GSM 1900/TDMS PCS/CDMA PCS	1850 MHz – 1910 MHz	DP-1900
TDMA (NADC)/AMPS	824 MHz – 849 MHz	DP-800
W-CDMA	1920 MHz – 1980 MHz	DP-2000
Korean CDMA	1715 MHz – 1780 MHz	DP-1700
101 Current Creek Band - Coder Dark	T_{2}	- FAV 1 510 050 074

1101 Cypress Creek Road 🖷 Cedar Park, Texas 78613, USA 🖷 1-512-258-9478 🔳 FAX 1-512-258-0740




DP-Series Precision Dipole Antennas

Communications Applications, continued			
ISM (Bluetooth)	2400 - 2483.5 MHz	DP2400	
Japan - Low Band	898 MHz – 901 MHz	DP-900-J 1	
	915 MHz – 940 MHz	DP-900-J2	
	940 MHz – 960 MHz	DP-900-J3	
Japan - High Band	1429 MHz – 1453 MHz	DP-1400	

Representative Data

A ANTENNAS



Mechanical Specifications

Dimensions:	Dependent on operating frequency; approx. one- half wavelength	
Weight:	Varies by model	
Construction:	Available in aluminum, stainless steel or brass	
RF Connector:	SMA (female)	

Ordering Information

Product:	Dipole Antenna
Model Number:	DP-Series
Warranty:	1 year limited

To place an order or to learn more about the TDK RF Solutions products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Ro	d.	
Cedar Park, Texas 78613 USA		
Phone:	1-512-258-9478	
Fax:	1-512-258-0740	
E-mail:	info@tdkrf.com	
World Wide Web:	www.tdkrfsolutions.com	

		ΤΟΤΑ	L R F	EXI	PERT	I S E ^{T M}
Electrical Specifications		S	C	Р	SW	TS
Gain:	See data graph	SYSTEMS	CHAMBERS	PRODUCTS	SOFTWARE	TEST SERVICES
Impedance	50 Ω		www.tdkrfsolutions.com			

To learn more about TDK RF Solutions' wide range of innovative products and services visit www.tdkrfsolutions.com

© Copyright 2004 TDK RF Solutions Inc. All rights reserved. Specifications subject to change without notice.