


XBee® & XBee-PRO® DigiMesh® 2.4

Mesh Networking Embedded RF Modules for OEMs

Embedded RF modules deliver wireless connectivity using the innovative and easy-to-deploy DigiMesh protocol.




Overview

XBee and XBee-PRO DigiMesh 2.4 embedded RF modules provide wireless connectivity to electronic devices using a globally deployable 2.4 GHz transceiver. These modules use the DigiMesh networking protocol. This innovative, peer-to-peer network offers users added network stability through self-healing, dense network operation and support for sleeping routers, extending the operational life of battery dependent networks.

XBee modules are ideal for low-power, low-cost applications. XBee-PRO modules are power-amplified versions of XBee modules for extended-range applications. Products in the XBee family are easy to use, share a common hardware footprint, and are fully interoperable with other XBee products utilizing the same technology. They are available in a variety of different protocols to suit different applications, enabling users to substitute one XBee module for another with minimal development time and risk.

Digi's unsurpassed offering of Drop-in Networking products provide users with seamless communication between devices. XBee adapters deliver wireless connectivity to electronic devices in wired networks. ConnectPort® X gateways enable users to access and configure remote devices in a network.

Application Highlight




Features/Benefits

- No configuration needed for out-of-the-box RF communications
- Common XBee footprint for a variety of RF modules
- Simple topology to deploy and grow
- 2.4 GHz for worldwide deployment
- Low-power XBee or extended-range XBee-PRO (pin/over-the-air compatible)
- Multiple antenna options
- Outdoor RF line-of-sight range up to 1 mile (1.6 km) with high-gain antennas
- DigiMesh peer-to-peer mesh networking protocol
 - Self-healing and discovery for network stability
 - Sleeping routers supported for long battery life

Related Products



Gateways



Modules



Adapters



Dev Kits



Range Extenders




Sensors



www.digi.com

Platform	XBee® DigiMesh® 2.4		XBee-PRO® DigiMesh® 2.4	XBee-PRO® DigiMesh® 2.4 (Int'l)
Performance				
RF Data Rate	250 Kbps			
Indor/Urban Range	100 ft (30 m)	300 ft (90 m)	200 ft (60 m)	
Outdoor/RF Line-of-Sight Range	300 ft (90 m)	1 mile (1.6 km)	2500 ft (750 m)	
Transmit Power	1 mW (+0 dBm)	63 mW (+18 dBm)	10 mW (+10 dBm)	
Receiver Sensitivity (1% PER)	-92 dBm	-100 dBm		
Features				
Serial Data Interface	3.3V CMOS serial UART			
Configuration Method	AT & API			
Frequency Band	2.4 GHz ISM			
Interference Immunity	DSSS (Direct Sequence Spread Spectrum)			
Serial Data Rate	Up to 115.2 Kbps			
ADC Inputs	(6) 10-bit ADC inputs			
Digital I/O	13			
Antenna Options	Chip, Wire Whip, U.FL, RPSMA			
Networking & Security				
Encryption	128-bit AES			
Reliable Packet Delivery	Retries/Acknowledgments			
Addressing Options	PAN ID, channel, 64-bit address			
Channels	16	12		
Power Requirements				
Supply Voltage	2.8 – 3.4VDC			
Transmit Current	45 mA	250 mA (Wire, Chip, U.FL), 340 mA (RPSMA)	150 mA (Wire, Chip, U.FL), 180 mA (RPSMA)	
Receive Current	50 mA	55 mA		
Power-Down Current	<50 uA			
Regulatory Approvals				
FCC (USA)	Yes			
IC (Canada)	Yes			
ETSI (Europe)	Yes	Yes (Max Tx 10 mW)	Yes	
C-TICK Australia	Yes			
Telec (Japan)	Yes	No	Yes	



Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong one-year warranty. www.digi.com/support

Digi International 877-912-3444 952-912-3444 email: info@digi.com	Digi International France +33-1-55-61-98-98 www.digi.fr	Digi International KK +81-3-5428-0261 www.digi-intl.co.jp	Digi International (HK) Limited +852-2833-1008 www.digi.cn
--	---	---	--

91001486
82/111

MAKING Wireless M2M EASY™

BUY ONLINE • www.digi.com

© 2008-2011 Digi International Inc. All rights reserved. Digi, Digi International, the Digi logo, the Making Wireless M2M Easy logo, ConnectPort, DigiMesh, XBee and XBee-PRO are trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective owners. All information provided is subject to change without notice.

