Product Brief: BHCRS02BI



# *Bluetooth*<sup>®</sup> RS232 Adapter

# HERE'S BON HURD

# Part No: BHCRS02BI

The EZURIO RS232 Adapter allows any device with a standard DB9 RS232 to upgrade to *Bluetooth* wireless connectivity. Using an EZURIO pre-approved module means no further approval required. Combined with our AT style interface this brings versatile adaptation to cable replacement within easy reach.

#### **Key Features**

- Class 1 "Plug-in" Bluetooth device
- Range up to 250 metres
- Simple AT style interface
- Integrated antenna
- Industrial temperature range -40°C to +85° operational range
- Fully approved standalone product no further approval cost
- Embedded Bluetooth stack
- Field upgradeable
- Remote configurable
- Profile support including: SPP, DUN, FTP client
- 2 year warranty

This product has been designed as a true industrial adapter, with an exceptional range of up to 250 metres ensuring a reliable and robust connection regardless of the environment, thus allowing connection to any other *Bluetooth* device using the same profile. The *Bluetooth* RS232 Adapter can be used as a direct cable replacement in any application utilising an RS232 port.

#### Key Benefits

- Fastest time to market
- Rugged design
- Low power
- Low cost of ownership
- No host stack required
- Fully approved

The *Bluetooth* RS232 Adapter supports all the major serial profiles including the Serial Port, Dial up Networking and FTP client.

# **Bluetooth RS232 Adapter**

#### **Features**

Features
Version 1.1 Bluetooth
9 pin female D type connector
Fully approved standalone product – No approval cost
Designed for any RS232 port cable replacement
Integrated antenna with up to 250m range
Sleek design with a cable for external cabinet mounting
Low current consumption
Data rates up to 250 kbps
Industrial Temperature range
Wide ranging profile support: SPP, DUN, and FTP client
Multipoint supported
Field upgradeable
2 Year warranty



## Key benefits

Fastest time to market	Ergonomically designed	Sup	ports encrypted data	Low power consumption
Lowest cost of ownership	Direct RS232 replacement	Rob	ust design	Extensive technical support

### Overview of the technical specification

Feature	Implementation
Bluetooth	Class 1
Frequency	2.400 – 2.485 GHz
Max Transmit Power	+ 6dBm
Min Transmit Power	- 27dBm
Idle Power	88mA typical
Receive Sensitivity	Better than -85dB

Feature	Implementation
Physical Size	102 X 54 X 5 mm, 30g
Bluetooth Qualified	Bluetooth 1.1
Temperature Range	-40°C to +85°
Multipoint	Option
Range	250m (free space)
Power Range	

The details contained within the document are subject to change; please download the product specification available from www.ezurio.com for the most up to date specification

For further information please visit our website at <u>www.ezurio.com</u> Alternatively contact: <u>sales@ezurio.com</u> - 2 + 44 (0) 20 8938 1072 Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA and licensed to EZURIO Ltd.