


ZMN2430 2.4GHZ SINGLE CHIP ZIGBEE™ WIRELESS MESH NETWORKING MODULE

Small in size, the low cost ZMN2430 module is ideal for ZigBee applications needing very low current consumption including industrial sensors, building and home automation, and any other applications requiring ZigBee's unique capabilities. The 2.4GHz, license-free band is also more widely accepted internationally. Based on the CC2430 SoC, the sleep current is less than 3uA for the entire module.



ZigBee/802.15.4. The ZMN2430 includes the ZigBee 2006 stack as well as Cirronet's CSM profile eliminating the need for any firmware development. The ZMN2430 can operate as a reduced function device (RFD) for end devices to consume the least amount of power, or as a full function device (FFD) to act as a Coordinator or Router. Each node type can be ordered separately or the module's bootloader can be used to load the appropriate firmware during manufacture.

Industrial Networking. With 1mW (0dBm) of transmit power has the power to communicate in industrial and high noise environments while minimizing the power consumed. The ZMN2430 also has a full industrial temperature operating range, -40°C to +85°C. Building on Cirronet's many years of developing products for industrial applications, the ZMN2430 is uniquely designed with Cirronet's proprietary technology that guarantees industrial grade performance.

Rapid & Cost-Effective Integration. The ZMN2430 is treated just like other integrated circuits. Even though it is a complete RF module, it is reflow soldered to the host PCB - there is no need for expensive, unreliable connectors and with its small

footprint, there is no size penalty for using a module. Cirronet has relied on its experience in helping hundreds of OEMs integrate Cirronet modules to create a full set of development and configuration tools.

FCC & ETSI Certifications. Cirronet has obtained FCC and ETSI certifications as a module. This means FCC & CE type acceptance testing is not required for the device into which the module is integrated, saving you money and getting your product to market faster.

Experience. Cirronet's 20 years of experience in RF goes into every ZMN2430 module. Our RF know-how and practical engineering have made Cirronet the choice of hundreds of OEMs. OEMs know they can rely on Cirronet products and Cirronet's unsurpassed technical support to help get their products to market on time.

Let us be your experts. Cirronet has delivered high-performance wireless products since 1987. To find out how to put our experience to work for you, call **+1.678.684.2000** or visit our website at **www.cirronet.com**.

FEATURES:

- 2.4 GHz Direct Sequence Spread Spectrum technology
- Ad hoc mesh network
- Small size, light weight
- FCC & ETSI certified for unlicensed operation

BENEFITS:

- Worldwide license-free operation
- Redundant, self healing network
- Supports large number of nodes
- Ideal for noisy, industrial applications
- Easy to integrate
- Shortens time to market
- Low cost



CIRRONET.
An RF Monolithics Company

ZMN2430 SPECIFICATIONS

GENERAL SPECIFICATIONS

RF Frequency	2401 - 2475 MHz
Spreading Method	Direct Sequence
Modulation	O-QPSK
Transmit Power	0dBm into 50 ohms (Software adjustable from -20dBm to 0dBm)
Receive Sensitivity	-95 dBm for 10 ⁻⁵ BER
RF Channels	16
RF Data Rate	250 Kbps
I/O	1 – SPI Port 6 – General purpose I/O lines 3 – 7 - 12-bit ADCs 2 – PWMs 1 – UART
Operating Voltage	3.3Vdc – 5.5Vdc
Current Consumption	Sleep – <3 μ A@3.3V typical Receive – 30 mA@3.3V typical Transmit – 25 mA@3.3V typical
Operating Temperature	-40°C to +85°C

CONNECTOR PINOUT

Pin 1 - GND	Pin 30 - GND
Pin 2 - RSVD	Pin 29 - RFIO
Pin 3 - RSVD	Pin 28 - GND
Pin 4 - GPIO0	Pin 27 - NC
Pin 5 - UART_TX	Pin 26 - NC
Pin 6 - UART_RX	Pin 25 - ADC REF
Pin 7 - GPIO4	Pin 24 - ADCZ
Pin 8 - GPIO5	Pin 23 - SPI_SCLK
Pin 9 - PWMA	Pin 22 - SPI_EN
Pin 10 - GPIO2	Pin 21 - SPI_MOSI
Pin 11 - GPIO1	Pin 20 - SPI_MISO
Pin 12 - GPIO3	Pin 19 - ADCY
Pin 13 - PWMB	Pin 18 - ADCX
Pin 14 - VCC	Pin 17 - /RESET
Pin 15 - GND	Pin 16 - GND

PHYSICAL SPECIFICATIONS

ZMN2430 Outline and Mounting Dimensions

