



### Intellimod™ L-Series Three Phase IGBT Inverter 25 Amperes/1200 Volts



**TERMINAL CODE**

- 1 VUPC
- 2 UFO
- 3 UP
- 4 VUP1
- 5 VVPC
- 6 VFO
- 7 VP
- 8 VVP1
- 9 VVWP
- 10 WFO
- 11 WP
- 12 VVWP1
- 13 VNC
- 14 VN1
- 15 NC
- 16 UN
- 17 VN
- 18 WN
- 19 FO



**Description:**  
Powerex Intellimod™ Intelligent Power Modules are isolated base modules designed for power switching applications operating at frequencies to 20kHz. Built-in control circuits provide optimum gate drive and protection for the IGBT and free-wheel diode power devices.

- Features:**
- Complete Output Power Circuit
  - Gate Drive Circuit
  - Protection Logic
    - Short Circuit
    - Over Temperature Using On-chip Temperature Sensing
    - Under Voltage
  - Low Loss Using 5th Generation IGBT Chip

- Applications:**
- Inverters
  - UPS
  - Motion/Servo Control
  - Power Supplies

**Ordering Information:**  
Example: Select the complete part number from the table below -i.e. PM25CLA120 is a 1200V, 25 Ampere Intellimod™ Intelligent Power Module.

Outline Drawing and Circuit Diagram

| Dimensions | Inches | Millimeters |
|------------|--------|-------------|
| A          | 4.72   | 120.0       |
| B          | 2.17   | 55.0        |
| C          | 0.63   | 16.0        |
| D          | 4.17   | 106.0       |
| E          | 0.28   | 7.0         |
| F          | 0.78   | 19.75       |
| G          | 2.62   | 66.5        |
| H          | 0.13   | 3.25        |
| J          | 0.63   | 16.0        |
| K          | 0.08   | 2.0         |
| L          | 0.10   | 2.5         |
| M          | 2.81   | 71.5        |
| N          | 0.20   | 5.0         |
| P          | 0.43   | 11.0        |
| Q          | 0.42   | 10.75       |
| R          | 0.87   | 22.0        |

| Dimensions | Inches    | Millimeters |
|------------|-----------|-------------|
| S          | 0.46      | 11.75       |
| T          | 0.59      | 15.0        |
| U          | 0.91      | 23.0        |
| V          | 0.57      | 14.5        |
| W          | 1.26      | 32.0        |
| X          | 1.22      | 31.0        |
| Y          | 0.69      | 17.5        |
| Z          | 1.14      | 29.0        |
| AA         | 0.51      | 13.0        |
| AB         | M5 Metric | M5          |
| AC         | 0.22 Dia. | Dia. 5.5    |
| AD         | 0.28      | 7.0         |
| AE         | 0.08      | 2.0         |
| AF         | 0.02 Sq.  | Sq. 0.5     |
| AG         | 0.10 Dia. | Dia. 2.5    |

| Type | Current Rating<br>Amperes | V <sub>CES</sub><br>Volts (x 10) |
|------|---------------------------|----------------------------------|
| PM   | 25                        | 120                              |

**PM25CLA120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**25 Amperes/1200 Volts**

## Absolute Maximum Ratings, $T_j = 25^\circ\text{C}$ unless otherwise specified

| Characteristics   | Symbol                 | PM25CLA120 | Units            |
|---|------------------------|------------|------------------|
| Power Device Junction Temperature   | $T_j$                  | -20 to 150 | $^\circ\text{C}$ |
| Storage Temperature   | $T_{\text{stg}}$       | -40 to 125 | $^\circ\text{C}$ |
| Mounting Torque, M5 Mounting Screws   | —                      | 31         | in-lb            |
| Mounting Torque, M5 Main Terminal Screws                                    | —                      | 31         | in-lb            |
| Module Weight (Typical)   | —                      | 380        | Grams            |
| Supply Voltage, Surge (Applied between P - N)                               | $V_{\text{CC(surge)}}$ | 1000       | Volts            |
| Self-protection Supply Voltage Limit (Short Circuit protection Capability)* | $V_{\text{CC(prot.)}}$ | 800        | Volts            |
| Isolation Voltage, AC 1 minute, 60Hz Sinusoidal                             | $V_{\text{ISO}}$       | 2500       | Volts            |

\*VD = 13.5 ~ 16.5V, Inverter Part,  $T_j = 125^\circ\text{C}$

## IGBT Inverter Sector

|  |                     |      |         |
|--|---------------------|------|---------|
| Collector-Emitter Voltage ( $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$ ) | $V_{\text{CES}}$    | 1200 | Volts   |
| Collector Current ( $T_C = 25^\circ\text{C}$ )                                   | $\pm I_C$           | 25   | Amperes |
| Peak Collector Current ( $T_C = 25^\circ\text{C}$ )                              | $\pm I_{\text{CP}}$ | 50   | Amperes |
| Collector Dissipation ( $T_C = 25^\circ\text{C}$ )                               | $P_C$               | 116  | Watts   |

## Control Sector

|  |                  |    |       |
|--|------------------|----|-------|
| Supply Voltage (Applied between $V_{\text{UP1}}-V_{\text{UPC}}$ , $V_{\text{VP1}}-V_{\text{VPC}}$ , $V_{\text{WP1}}-V_{\text{WPC}}$ , $V_{\text{N1}}-V_{\text{NC}}$ )    | $V_D$            | 20 | Volts |
| Input Voltage (Applied between $U_P-V_{\text{UPC}}$ , $V_P-V_{\text{VPC}}$ , $W_P-V_{\text{WPC}}$ , $U_N-V_N$ , $W_N-V_{\text{NC}}$ )                                    | $V_{\text{CIN}}$ | 20 | Volts |
| Fault Output Supply Voltage<br>(Applied between $U_{\text{FO}}-V_{\text{UPC}}$ , $V_{\text{FO}}-V_{\text{VPC}}$ , $W_{\text{FO}}-V_{\text{WPC}}$ , $F_O-V_{\text{NC}}$ ) | $V_{\text{FO}}$  | 20 | Volts |
| Fault Output Current ( $U_{\text{FO}}$ , $V_{\text{FO}}$ , $W_{\text{FO}}$ , $F_O$ Terminals)  | $I_{\text{FO}}$  | 20 | mA    |

**PM25CLA120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**25 Amperes/1200 Volts**

**Electrical and Mechanical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**


| Characteristics                      | Symbol        | Test Conditions   | Min. | Typ. | Max. | Units         |
|--------------------------------------|---------------|---|------|------|------|---------------|
| <b>IGBT Inverter Sector</b>          |               |   |      |      |      |               |
| Collector-Emitter Cutoff Current     | $I_{CES}$     | $V_{CE} = V_{CES}, V_D = 15V, T_j = 25^\circ\text{C}$         | —    | —    | 1.0  | mA            |
|                                      |               | $V_{CE} = V_{CES}, V_D = 15V, T_j = 125^\circ\text{C}$        | —    | —    | 10   | mA            |
| Diode Forward Voltage                | $V_{EC}$      | $-I_C = 25A, V_{CIN} = 15V, V_D = 15V$                        | —    | 2.5  | 3.5  | Volts         |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_D = 15V, V_{CIN} = 0V, I_C = 25A, T_j = 25^\circ\text{C}$  | —    | 1.8  | 2.3  | Volts         |
|                                      |               | $V_D = 15V, V_{CIN} = 0V, I_C = 25A, T_j = 125^\circ\text{C}$ | —    | 1.9  | 2.4  | Volts         |
| Inductive Load Switching Times       | $t_{on}$      |   | 0.5  | 1.0  | 2.5  | $\mu\text{s}$ |
|                                      | $t_{rr}$      | $V_D = 15V, V_{CIN} = 0 \Leftrightarrow 15V$                  | —    | 0.5  | 0.8  | $\mu\text{s}$ |
|                                      | $t_{C(on)}$   | $V_{CC} = 600V, I_C = 25A$                                    | —    | 0.4  | 1.0  | $\mu\text{s}$ |
|                                      | $t_{off}$     | $T_j = 125^\circ\text{C}$                                     | —    | 2.0  | 3.0  | $\mu\text{s}$ |
|                                      | $t_{C(off)}$  |   | —    | 0.7  | 1.2  | $\mu\text{s}$ |

**Control Sector**

|  |               |  |      |      |      |                  |
|--|---------------|--|------|------|------|------------------|
| Short Circuit Trip Level   | SC            | $-20^\circ\text{C} \leq T_j \leq 125^\circ\text{C}, V_D = 15V$ | 50   | —    | —    | Amperes          |
| Short Circuit Current Delay Time   | $t_{off(SC)}$ | $V_D = 15V$  | —    | 0.2  | —    | $\mu\text{s}$    |
| Over Temperature Protection<br>(Detect $T_j$ of IGBT Chip)                           | OT            | Trip Level   | 135  | 145  | 155  | $^\circ\text{C}$ |
|  | $OT_R$        | Reset Level  | —    | 125  | —    | $^\circ\text{C}$ |
| Supply Circuit Under-voltage Protection<br>( $-20 \leq T_j \leq 125^\circ\text{C}$ ) | UV            | Trip Level   | 11.5 | 12.0 | 12.5 | Volts            |
|  | $UV_R$        | Reset Level  | —    | 12.5 | —    | Volts            |
| Circuit Current  | $I_D$         | $V_D = 15V, V_{CIN} = 15V, V_{N1}-V_{NC}$                      | —    | 15   | 25   | mA               |
|  |               | $V_D = 15V, V_{CIN} = 15V, V_{XP1}-V_{XPC}$                    | —    | 5    | 10   | mA               |
| Input ON Threshold Voltage   | $V_{th(on)}$  | Applied between $U_P-V_{UPC}$ ,                                | 1.2  | 1.5  | 1.8  | Volts            |
| Input OFF Threshold Voltage  | $V_{th(off)}$ | $V_P-V_{VPC}, W_P-V_{WPC}, U_N-V_{N-}, W_N-V_{NC}$             | 1.7  | 2.0  | 2.3  | Volts            |
| Fault Output Current*  | $I_{FO(H)}$   | $V_D = 15V, V_{CIN} = 15V$                                     | —    | —    | 0.01 | mA               |
|  | $I_{FO(L)}$   | $V_D = 15V, V_{CIN} = 15V$                                     | —    | 10   | 15   | mA               |
| Fault Output Pulse Width*  | $t_{FO}$      | $V_D = 15V$  | 1.0  | 1.8  | —    | ms               |

\*Fault output is given only when the internal SC, OT and UV protections schemes of either upper or lower device operate to protect it.

**$T_C$  Measurement Point**



| Axis \ Arm | UP   |      | VP   |      | WP   |      | UN   |      | VN   |      | WN   |      |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|
|            | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi |
| X          | 29.0 | 29.3 | 64.0 | 65.5 | 85.6 | 85.9 | 37.8 | 37.5 | 55.2 | 55.7 | 75.8 | 75.3 |
| Y          | -7.1 | 1.5  | -7.1 | 2.0  | -7.1 | 2.0  | 5.1  | -4.5 | 5.1  | -4.5 | 5.1  | -4.5 |

**PM25CLA120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**25 Amperes/1200 Volts**

## Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

| Characteristics                     | Symbol         | Test Conditions                                   | Min. | Typ. | Max.  | Units                 |
|-------------------------------------|----------------|---|------|------|-------|-----------------------|
| <b>Thermal Characteristics</b>      |                |   |      |      |       |                       |
| Characteristic                      | Symbol         | Condition   | Min. | Typ. | Max.  | Units                 |
| Junction to Case Thermal Resistance | $R_{th(j-c)Q}$ | IGBT (Per 1/6 Module)                             | —    | —    | 0.83* | $^\circ\text{C/Watt}$ |
|                                     | $R_{th(j-c)D}$ | FWDi (Per 1/6 Module)                             | —    | —    | 1.36* | $^\circ\text{C/Watt}$ |
| Contact Thermal Resistance          | $R_{th(c-f)}$  | Case to Fin Per Module,<br>Thermal Grease Applied | —    | —    | 0.038 | $^\circ\text{C/Watt}$ |


\* If you use this value,  $R_{th(f-a)}$  should be measured just under the chips.

## Recommended Conditions for Use

| Characteristic                  | Symbol         | Condition  | Value          | Units         |
|---------------------------------|----------------|--|----------------|---------------|
| Supply Voltage                  | $V_{CC}$       | Applied across P-N Terminals   | $\leq 800$     | Volts         |
| Control Supply Voltage**        | $V_D$          | Applied between $V_{UP1}-V_{UPC}$ ,<br>$V_{VP1}-V_{VPC}$ , $V_{WP1}-V_{WPC}$ , $V_{N1}-V_{NC}$ | $15.0 \pm 1.5$ | Volts         |
| Input ON Voltage                | $V_{CIN(on)}$  | Applied between $U_P-V_{UPC}$ ,  | $\leq 0.8$     | Volts         |
| Input OFF Voltage               | $V_{CIN(off)}$ | $V_P-V_{VPC}$ , $W_P-V_{WPC}$ , $U_N-V_N$ , $W_N-V_{NC}$                                       | $\geq 9.0$     | Volts         |
| PWM Input Frequency             | $f_{PWM}$      | —  | $\leq 20$      | kHz           |
| Arm Shoot-through Blocking Time | $t_{DEAD}$     | Input Signal   | $\geq 2.5$     | $\mu\text{s}$ |

\*\* With ripple satisfying the following conditions:  $dv/dt$  swing  $\leq \pm 5V/\mu\text{s}$ , Variation  $\leq 2V$  peak to peak.

**PM25CLA120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
 25 Amperes/1200 Volts



**PM25CLA120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
 25 Amperes/1200 Volts

