



### Intellimod™ L-Series Three Phase IGBT Inverter 50 Amperes/1200 Volts



**TERMINAL CODE**

- 1 VUPC
- 2 UFO
- 3 UP
- 4 VUP1
- 5 VVPC
- 6 VFO
- 7 VP
- 8 VVP1
- 9 WVPC
- 10 WFO
- 11 WP
- 12 WVP1
- 13 VNC
- 14 VNI
- 15 NC
- 16 UN
- 17 VN
- 18 WN
- 19 FO



**Description:**

Powerex Intellimod™ Intelligent Power Modules are isolated base modules designed for power switching applications operating at frequencies to 20kHz. Built-in control circuits provide optimum gate drive and protection for the IGBT and free-wheel diode power devices.

**Features:**

- Complete Output Power Circuit
- Gate Drive Circuit
- Protection Logic
  - Short Circuit
  - Over Temperature
  - Using On-chip Temperature Sensing
  - Under Voltage
- Low Loss Using 5th Generation IGBT Chip

**Applications:**

- Inverters
- UPS
- Motion/Servo Control
- Power Supplies

**Ordering Information:**

Example: Select the complete part number from the table below -i.e. PM50CLB120 is a 1200V, 50 Ampere Intellimod™ Intelligent Power Module.

| Type | Current Rating<br>Amperes | V <sub>CES</sub><br>Volts (x 10) |
|------|---------------------------|----------------------------------|
| PM   | 50                        | 120                              |

**Outline Drawing and Circuit Diagram**

| Dimensions | Inches | Millimeters |
|------------|--------|-------------|
| A          | 4.72   | 120.0       |
| B          | 2.17   | 55.0        |
| C          | 0.63   | 16.0        |
| D          | 4.17   | 106.0       |
| E          | 0.28   | 7.0         |
| F          | 0.78   | 19.75       |
| G          | 2.62   | 66.5        |
| H          | 0.13   | 3.25        |
| J          | 0.63   | 16.0        |
| K          | 0.08   | 2.0         |
| L          | 0.10   | 2.5         |
| M          | 2.81   | 71.5        |
| N          | 0.20   | 5.0         |
| P          | 0.31   | 7.75        |
| Q          | 3.87   | 98.25       |
| R          | 0.87   | 22.0        |
| S          | 0.10   | 2.5         |
| T          | 0.77   | 19.5        |
| U          | 0.91   | 23.0        |

| Dimensions | Inches    | Millimeters |
|------------|-----------|-------------|
| V          | 0.16      | 4.0         |
| W          | 1.01      | 25.75       |
| X          | 2.00      | 50.75       |
| Y          | 0.69      | 17.5        |
| Z          | 0.30      | 7.5         |
| AA         | 0.98      | 25.0        |
| AB         | 0.10 Dia. | Dia. 2.5    |
| AC         | 0.22 Dia. | Dia. 5.5    |
| AD         | 0.67      | 17.0        |
| AE         | 0.10 Dia. | Dia. 2.5    |
| AF         | 0.33      | 8.5         |
| AG         | 0.08      | 2.0         |
| AH         | 0.41      | 10.5        |
| AJ         | 1.08      | 27.5        |
| AK         | 0.04      | 1.0         |
| AL         | 0.02 Sq.  | Sq. 0.5     |
| AM         | 0.06      | 1.5         |
| AN         | 0.04      | 1.0         |

**PM50CLB120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**50 Amperes/1200 Volts**

**Absolute Maximum Ratings,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

| Characteristics   | Symbol                 | PM50CLB120 | Units            |
|---|------------------------|------------|------------------|
| Power Device Junction Temperature   | $T_j$                  | -20 to 150 | $^\circ\text{C}$ |
| Storage Temperature   | $T_{\text{stg}}$       | -40 to 125 | $^\circ\text{C}$ |
| Mounting Torque, M5 Mounting Screws   | —                      | 31         | in-lb            |
| Module Weight (Typical)   | —                      | 340        | Grams            |
| Supply Voltage, Surge (Applied between P - N)                               | $V_{\text{CC(surge)}}$ | 1000       | Volts            |
| Self-protection Supply Voltage Limit (Short Circuit protection Capability)* | $V_{\text{CC(prot.)}}$ | 800        | Volts            |
| Isolation Voltage, AC 1 minute, 60Hz Sinusoidal                             | $V_{\text{ISO}}$       | 2500       | Volts            |

\*VD = 13.5 ~ 16.5V, Inverter Part,  $T_j = 125^\circ\text{C}$

**IGBT Inverter Sector**

|  |                     |      |         |
|--|---------------------|------|---------|
| Collector-Emitter Voltage ( $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$ ) | $V_{\text{CES}}$    | 1200 | Volts   |
| Collector Current ( $T_C = 25^\circ\text{C}$ )                                   | $\pm I_C$           | 50   | Amperes |
| Peak Collector Current ( $T_C = 25^\circ\text{C}$ )                              | $\pm I_{\text{CP}}$ | 100  | Amperes |
| Collector Dissipation ( $T_C = 25^\circ\text{C}$ )                               | $P_C$               | 369  | Watts   |

**Control Sector**

|  |                  |    |       |
|--|------------------|----|-------|
| Supply Voltage (Applied between $V_{\text{UP1}}-V_{\text{UPC}}$ , $V_{\text{VP1}}-V_{\text{VPC}}$ , $V_{\text{WP1}}-V_{\text{WPC}}$ , $V_{\text{N1}}-V_{\text{NC}}$ )    | $V_D$            | 20 | Volts |
| Input Voltage (Applied between $U_P-V_{\text{UPC}}$ , $V_P-V_{\text{VPC}}$ , $W_P-V_{\text{WPC}}$ , $U_N-V_{\text{NC}}$ , $V_N-V_{\text{NC}}$ )                          | $V_{\text{CIN}}$ | 20 | Volts |
| Fault Output Supply Voltage<br>(Applied between $U_{\text{FO}}-V_{\text{UPC}}$ , $V_{\text{FO}}-V_{\text{VPC}}$ , $W_{\text{FO}}-V_{\text{WPC}}$ , $F_O-V_{\text{NC}}$ ) | $V_{\text{FO}}$  | 20 | Volts |
| Fault Output Current ( $U_{\text{FO}}$ , $V_{\text{FO}}$ , $W_{\text{FO}}$ , $F_O$ Terminals)  | $I_{\text{FO}}$  | 20 | mA    |

**Electrical and Mechanical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

| Characteristics                      | Symbol               | Test Conditions  | Min. | Typ. | Max. | Units         |
|--------------------------------------|----------------------|--|------|------|------|---------------|
| Collector-Emitter Cutoff Current     | $I_{\text{CES}}$     | $V_{\text{CE}} = V_{\text{CES}}$ , $V_D = 15\text{V}$ , $T_j = 25^\circ\text{C}$   | —    | —    | 1.0  | mA            |
|                                      |                      | $V_{\text{CE}} = V_{\text{CES}}$ , $V_D = 15\text{V}$ , $T_j = 125^\circ\text{C}$  | —    | —    | 10   | mA            |
| Diode Forward Voltage                | $V_{\text{EC}}$      | $-I_C = 50\text{A}$ , $V_{\text{CIN}} = 15\text{V}$ , $V_D = 15\text{V}$   | —    | 2.5  | 3.5  | Volts         |
| Collector-Emitter Saturation Voltage | $V_{\text{CE(sat)}}$ | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 0\text{V}$ , $I_C = 50\text{A}$ ,<br>$T_j = 25^\circ\text{C}$                             | —    | 1.8  | 2.3  | Volts         |
|                                      |                      | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 0\text{V}$ , $I_C = 50\text{A}$ ,<br>$T_j = 125^\circ\text{C}$                            | —    | 1.9  | 2.4  | Volts         |
| Inductive Load Switching Times       | $t_{\text{on}}$      | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 0$ 15V<br>$V_{\text{CC}} = 600\text{V}$ , $I_C = 50\text{A}$<br>$T_j = 125^\circ\text{C}$ | 0.5  | 1.0  | 2.5  | $\mu\text{s}$ |
|                                      | $t_{\text{rr}}$      |  | —    | 0.5  | 0.8  | $\mu\text{s}$ |
|                                      | $t_{\text{C(on)}}$   |  | —    | 0.4  | 1.0  | $\mu\text{s}$ |
|                                      | $t_{\text{off}}$     |  | —    | 2.0  | 3.0  | $\mu\text{s}$ |
|                                      | $t_{\text{C(off)}}$  |  | —    | 0.7  | 1.2  | $\mu\text{s}$ |

**PM50CLB120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**50 Amperes/1200 Volts**

## Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

| Characteristics  | Symbol               | Test Conditions  | Min. | Typ. | Max. | Units            |
|--|----------------------|--|------|------|------|------------------|
| <b>Control Sector</b>  |                      |  |      |      |      |                  |
| Short Circuit Trip Level   | SC                   | $-20^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ , $V_D = 15\text{V}$             | 100  | —    | —    | Amperes          |
| Short Circuit Current Delay Time   | $t_{\text{off(SC)}}$ | $V_D = 15\text{V}$   | —    | 0.2  | —    | $\mu\text{s}$    |
| Over Temperature Protection<br>(Detect $T_j$ of IGBT Chip)                           | OT                   | Trip Level   | 135  | 145  | 155  | $^\circ\text{C}$ |
|  | $\text{OT}_R$        | Reset Level  | —    | 125  | —    | $^\circ\text{C}$ |
| Supply Circuit Under-voltage Protection<br>( $-20 \leq T_j \leq 125^\circ\text{C}$ ) | UV                   | Trip Level   | 11.5 | 12.0 | 12.5 | Volts            |
|  | $\text{UV}_R$        | Reset Level  | —    | 12.5 | —    | Volts            |
| Circuit Current  | $I_D$                | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$ , $V_{\text{N1}}-V_{\text{NC}}$   | —    | 15   | 25   | $\text{mA}$      |
|  |                      | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$ , $V_{\text{XP1}}-V_{\text{XPC}}$ | —    | 5    | 10   | $\text{mA}$      |
| Input ON Threshold Voltage   | $V_{\text{th(on)}}$  | Applied between $U_P-V_{\text{UPC}}$ ,   | 1.2  | 1.5  | 1.8  | Volts            |
| Input OFF Threshold Voltage  | $V_{\text{th(off)}}$ | $V_P-V_{\text{VPC}}$ , $W_P-V_{\text{WPC}}$ , $U_N-V_N$ , $W_N-V_{\text{NC}}$        | 1.7  | 2.0  | 2.3  | Volts            |
| Fault Output Current*  | $I_{\text{FO(H)}}$   | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$                                   | —    | —    | 0.01 | $\text{mA}$      |
|  | $I_{\text{FO(L)}}$   | $V_D = 15\text{V}$ , $V_{\text{CIN}} = 15\text{V}$                                   | —    | 10   | 15   | $\text{mA}$      |
| Fault Output Pulse Width*  | $t_{\text{FO}}$      | $V_D = 15\text{V}$   | 1.0  | 1.8  | —    | ms               |

\*Fault output is given only when the internal SC, OT and UV protections schemes of either upper or lower device operate to protect it.

## Thermal Characteristics


| Characteristic                      | Symbol                | Condition   | Min. | Typ. | Max.  | Units                 |
|-------------------------------------|-----------------------|---|------|------|-------|-----------------------|
| Junction to Case Thermal Resistance | $R_{\text{th(j-c)Q}}$ | IGBT (Per 1/6 Module)                             | —    | —    | 0.26  | $^\circ\text{C/Watt}$ |
|                                     | $R_{\text{th(j-c)D}}$ | FWDi (Per 1/6 Module)                             | —    | —    | 0.39  | $^\circ\text{C/Watt}$ |
| Contact Thermal Resistance          | $R_{\text{th(c-f)}}$  | Case to Fin Per Module,<br>Thermal Grease Applied | —    | —    | 0.038 | $^\circ\text{C/Watt}$ |

## Recommended Conditions for Use

| Characteristic                  | Symbol                | Condition   | Value          | Units         |
|---------------------------------|-----------------------|---|----------------|---------------|
| Supply Voltage                  | $V_{\text{CC}}$       | Applied across P-N Terminals  | $\leq 800$     | Volts         |
| Control Supply Voltage**        | $V_D$                 | Applied between $V_{\text{UP1}}-V_{\text{UPC}}$ ,   | $15.0 \pm 1.5$ | Volts         |
|                                 |                       | $V_{\text{VP1}}-V_{\text{VPC}}$ , $V_{\text{WP1}}-V_{\text{WPC}}$ , $V_{\text{N1}}-V_{\text{NC}}$ |                |               |
| Input ON Voltage                | $V_{\text{CIN(on)}}$  | Applied between $U_P-V_{\text{UPC}}$ ,  | $\leq 0.8$     | Volts         |
| Input OFF Voltage               | $V_{\text{CIN(off)}}$ | $V_P-V_{\text{VPC}}$ , $W_P-V_{\text{WPC}}$ , $U_N-V_N$ , $W_N-V_{\text{NC}}$                     | $\geq 9.0$     | Volts         |
| PWM Input Frequency             | $f_{\text{PWM}}$      | —   | $\leq 20$      | $\text{kHz}$  |
| Arm Shoot-through Blocking Time | $t_{\text{DEAD}}$     | Input Signal  | $\geq 2.5$     | $\mu\text{s}$ |

\*\* With ripple satisfying the following conditions:  $dv/dt$  swing  $\leq \pm 5\text{V}/\mu\text{s}$ , Variation  $\leq 2\text{V}$  peak to peak.


$T_C$  Measurement Point




| Arm<br>Axis | UP   |      | VP   |      | WP   |      | UN   |      | VN   |      | WN   |      |
|-------------|------|------|------|------|------|------|------|------|------|------|------|------|
|             | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi | IGBT | FWDi |
| X           | 28.3 | 28.4 | 65.0 | 64.9 | 87.0 | 86.9 | 39.3 | 39.2 | 54.0 | 54.1 | 76.0 | 76.1 |
| Y           | -7.7 | 1.5  | -7.7 | 1.5  | -7.7 | 1.5  | 5.7  | -3.5 | 5.7  | -3.5 | 5.7  | -3.5 |

**PM50CLB120**  
**Intellimod™ L-Series**  
**Three Phase IGBT Inverter**  
**50 Amperes/1200 Volts**


**COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)**




**FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)**




**REVERSE RECOVERY CHARACTERISTICS (TYPICAL)**




**REVERSE RECOVERY CHARACTERISTICS (TYPICAL)**



**SWITCHING LOSS (ON) VS. COLLECTOR CURRENT (TYPICAL)**



**SWITCHING LOSS (OFF) VS. COLLECTOR CURRENT (TYPICAL)**



**TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (IGBT & FWDi)**

