


Photomicrosensor (Transmissive) EE-SX1128


! Be sure to read *Precautions* on page 25.

■ Dimensions

Note: All units are in millimeters unless otherwise indicated.



Internal Circuit



Unless otherwise specified, the tolerances are as shown below.

Dimensions	Tolerance
$0 < x \leq 4$	± 0.100
$4 < x \leq 18$	± 0.200

Terminal No.	Name
A	Anode
K	Cathode
C	Collector
E	Emitter

■ Electrical and Optical Characteristics (Ta = 25°C)

Item	Symbol	Value	Condition
Emitter	Forward voltage	V _F	1.2 V typ., 1.5 V max. I _F = 30 mA
	Reverse current	I _R	0.01 μA typ., 10 μA max. V _R = 4 V
	Peak emission wavelength	λ _P	940 nm typ. I _F = 20 mA
Detector	Light current	I _L	0.5 mA min., 10 mA max. I _F = 20 mA, V _{CE} = 10 V
	Dark current	I _D	2 nA typ., 200 nA max. V _{CE} = 10 V, 0 lux
	Leakage current	I _{LEAK}	---
	Collector-Emitter saturated voltage	V _{CE} (sat)	0.1 V typ., 0.4 V max. I _F = 20 mA, I _L = 0.1 mA
	Peak spectral sensitivity wavelength	λ _P	850 nm typ. V _{CE} = 10 V
Rising time	tr	4 μs typ.	V _{CC} = 5 V, R _L = 100 Ω, I _L = 5 mA
Falling time	tf	4 μs typ.	V _{CC} = 5 V, R _L = 100 Ω, I _L = 5 mA

■ Features

- General-purpose model with a 4.2-mm-wide slot.
- PCB mounting type.
- High resolution with a 0.5-mm-wide aperture.
- Horizontal sensing aperture.


■ Absolute Maximum Ratings (Ta = 25°C)

	Item	Symbol	Rated value
Emitter	Forward current	I _F	50 mA (see note 1)
	Pulse forward current	I _{FP}	1 A (see note 2)
	Reverse voltage	V _R	4 V
Detector	Collector-Emitter voltage	V _{CEO}	30 V
	Emitter-Collector voltage	V _{ECO}	---
	Collector current	I _C	20 mA
	Collector dissipation	P _C	100 mW (see note 1)
Ambient temperature	Operating	T _{opr}	-25°C to 85°C
	Storage	T _{stg}	-30°C to 100°C
Soldering temperature		T _{sol}	260°C (see note 3)


- Note: 1. Refer to the temperature rating chart if the ambient temperature exceeds 25°C.
 2. The pulse width is 10 μs maximum with a frequency of 100 Hz.
 3. Complete soldering within 10 seconds.

■ Engineering Data


Forward Current vs. Collector Dissipation Temperature Rating




Light Current vs. Collector-Emitter Voltage Characteristics (Typical)




Response Time vs. Load Resistance Characteristics (Typical)




Response Time Measurement Circuit




Forward Current vs. Forward Voltage Characteristics (Typical)




Light Current vs. Forward Current Characteristics (Typical)



Dark Current vs. Ambient Temperature Characteristics (Typical)



Relative Light Current vs. Ambient Temperature Characteristics (Typical)



Sensing Position Characteristics (Typical)

