


- A. 10mm (.395") snap socket to ground work surface.
- B. Molded in black thermoplastic elastomer.
- C. Ring terminal, .200" ID, (#10).
- D. Extra ring terminal included for customizing length.
- E. The **09821** has a 1 megohm resistor between the snap and ground, with banana jacks at ground potential. The **09820** has no resistor between snap and ground, with banana jacks also at ground potential.
- F. Wire is autosplice crimped to secure it inside of the mold.
- G. High flex strand copper, 20 gauge, with PVC insulated jacket
09821 - black insulation
09820 - green insulation with yellow stripe
 OD = .100"
- H. Dual banana jacks at ground potential (.162" - .164" ± .002" ID).
- I. Desco and ground symbol molded into the plastic.
- J. Date coded to show month and year of manufacture. Arrow points to month of manufacture (12:00 = December), numerals indicate the year (03=2003).
 Grounds ESD Work Surface and Writ Strap to Common Point

ITEM	DESCRIPTION
09820	No Resistor - Green Wire with Yellow Stripe
09821	One Megohm Resistor to Mat - Black Wire



GROUND CORD, COMMON POINT, WORKMAT

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
 PHONE (909) 627-8178 FAX (909) 627-7449
 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
09820

DATE:
February
2010

©2010 DESCO INDUSTRIES INC.
Employee Owned

