

DESCO

Description:

This product is designed for use in ESD controlled areas where there are ESDsensitive devices. This product is constructed out of 6 mil, clear, permanently dissipative polyethylene film. Drawing protectors are designed to provide static control packaging for holding engineering drawings or other large documents. This product meets or exceeds the requirements of MIL-B-81705C, Type II.

Amine-free.
N-Octanoic acid free.
Humidity independent.
Does not promote corrosion.
Has no measurable outgassing.

Electrical Properties:

Static Decay: < 1.0 sec. per FTMS 101C, Method 4046

Surface Resistivity: 10¹⁰ - 10¹² Ohms/sq. per ASTM D-257

Specifications:

Polycarbonate haze: Negligible 72 hr contact

Corrosivity: Neglibible per FTMS 101C, Method 3005 Melt Index: .050 gm/10 min. per ASTM D-1238 0.923 gm/cc per ASTM D-1505 Density: 10% per ASTM D-1003 Haze: 60° gloss: 45° gloss: 90 per ASTM D-2457 56 per ASTM D-2457 per ASTM D-1709 Dart impact: 230 gms Coefficient of friction: per ASTM D-1894 0.50 1% secant modulus: MD 24,000 psi per ASTM D-882

Stiffness: MD 25,000 psi per ASTM D-882

A. B size drawing holder will hold up to an 11" x 17" sheet size.

Wording across bottom area:

"DESCO STATIC SAFE B SIZE DRAWING PROTECTOR ITEM #07453"

DRAWING PROTECTOR, STATIC SAFE, 6 MIL

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com PHONE (909) 627-8178 FAX (909) 627-71449 FAX REQUEST (909) 627-7126

DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172 DRAWING NUMBER

07453

DATE: 8/01

DESCO INDUSTRIES INC. Employee Owned