3MTM Wrist Strap -- Adjustable Fabric

Adjustable Fabric Wrist Strap

This wrist strap set features a fully adjustable, stretch elastic wristband and 6 or 12 ft coiled cord. The hypoallergenic, 85 ohm, silver-plated band provides 360 degree conductivity around the wrist for maximum skin contact. OptiSoft band fabric is extra-soft and avoids the scratchy feel of other bands. A machined snap provides a consistent 1 pound removal force. The polyurethane polymer strain reliefs survives 1 million flexes. Cord tangles are reduced by the "spinning style" banana plug. UL Listed. Made in the USA.



<u>Standards</u>

Meets or exceeds the requirements of ANSI/ESD S-1.1, ANSI/ESD S-20.20, EIA 625, MIL-STD-1686, and MIL-HDBK-263. MIL-STD-1686, and MIL-HDBK-263,

Specifications

Band

Fabric: OptiSoft Elastic Nylon with silver plated threads

85 ohms typical Resistance: Contact: 360 degrees around wrist

Color: Light Blue with white edges Snap: 4 mm machined post


Snap Release: 1 - 5 pounds Date Code Markings: Back plate Stainless Steel medical grade

Cord

Length: 6 or 12 feet, extended Resistor: 1 megohm

Flex life: 1 million flexes Color: Black

Markings: Date Code, resistance Banana Plug: Spinning, stainless Snap:



3M Wrist Strap and Cord -- Adjustable Fabric



Part Numbers

4mm (1/8") snap

WBB-AFWS Adjustable Fabric Wristband WBB-AFWS61M Adjustable Fabric Wristband and 6 ft cord WBB-AFWS121M Adjustable Fabric Wristband and 12 ft cord

CC61M 6 ft cord CC121M 12 ft cord 10mm (3/8") snap

WBB-AFWS-10 Adjustable Fabric Wristband WBB-AFWS61M-10 Adjustable Fabric Wristband and 6 ft cord WBB-AFWS121M-10 Adjustable Fabric Wristband and 12 ft cord CC61M-10 6 ft cord

CC121M-10 12 ft cord

CC61M-1010 6 ft cord, Stud to Stud CC121M-1010 12 ft cord, Stud to Stud



R O D U C D Α Н

Wrist Strap - Fabric Band PREMIUM PERFORMANCE

PRODUCT FABRIC BAND WRIST STRAP

ITEM NUMBER SEE ABOVE

DATASHEET 1114-A

3M Electronic Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735

Intl: 919-718-0000; Fax: 919-774-8174

email: 3Mstaticinfo@mmm.com; www.3M.com/static

3M is a trademark of 3M Company. All other trademarks herein are the property of their respective owners

© 2008

