

4





3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	BY	APP'D
AD	00	B	REVISED PER ECO-08-031349	16DEC08	HMR MW



SECTION A-A

- NOTES:
1. ALL COLORS AND MATERIALS MADE FROM ONE TOOL.
 2. SOME DIMENSIONS MAY VARY DUE TO DIFFERENT COMPOUND SHRINKAGE FACTOR.
 3. BLACK FINISH/NICKEL PLATING ON INSIDE THREADS REMOVED DUE TO MOLDING PROCESS PERMITTED.
 4. MINOR FLASH ACCEPTABLE ON INSERT THREAD.
 5. RUBBER TO METAL BOND MUST MEET OR EXCEED THE TENSILE STRENGTH OF RUBBER.
 6. RUBBER OVERLAY PERMISSIBLE OVER HEX FLATS AS SHOWN IN THE DRAWING.
 7. RUBBER OVERLAY PERMISSIBLE OVER HEX FLATS AS SHOWN IN THE DRAWING.
 8. TREAT WITH PERMANENT LUBRICANT.
 9. COMPONENTS MUST COMPLY WITH THE EUROPEAN DIRECTIVE 2002/95/EC ON RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (ROHS DIRECTIVE).

ALCO PART NUMBER	PART NUMBER	HEX NUT MATERIAL	RUBBER BOOT MATERIAL
BT1532004	1825600-1	BRASS, BLACK OXIDE PER MIL-F-495	SILICONE, COLOR BLACK
BT1532204	1825600-2	BRASS, NICKEL PLATE PER QQ-N-290	SILICONE, COLOR RED
BT1532804	1825600-3	BRASS, NICKEL PLATE PER QQ-N-290	SILICONE, COLOR GRAY

NO.	DESCRIPTION	DRAWING NO.	MATERIAL
①	NUT 15/32-32 UNS-2B	HEX NUT 15/32-32	BRASS, FINISH AS PER ABOVE TABLE
②	RUBBER BOOT	RUBBER BOOT	SILICONE PER 22-R-765 CLASS 3A, GRADE 50 COLOR AS PER ABOVE TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNED BY	R. BROWN	DATE	03JAN2008
CHECKED BY	M. WILBOURN	DATE	03JAN2008
APPROVED BY	M. WILBOURN	DATE	03JAN2008
PRODUCT SPEC	15/32-32 TOGGLE SWITCH BOOT SEAL		

TYCO ELECTRONICS CORPORATION
 HARRISBURG, PA 17105-3608

SIZE	A2	CAGE CODE	00779	DRAWING NO.	1825600	RESTRICTED TO	
WEIGHT							

CUSTOMER DRAWING SCALE: 3:1 SHEET: 1 of 1 REV: B

AMP 1471-9 REV 31MM2000

1825600

A