

multimec® 3A/4A + 1A/1H/1M/1ZA

Technical Data

- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
 - low temp: -40/+115°C
 - high temp: -40/+160°C



Keycaps shown on this page can also be used on **illumec™ switch 4A**

Dimensions (through-hole) 1A+3A	Dimensions (w/LED) 1H+3A	Dimensions (SMD) 1ZA+3A	Dimensions (SMD) 1M+3A
PCB layout 	PCB layout (top view) 	PCB layout 	PCB layout

How to order

3 A	<input type="checkbox"/>	<input type="checkbox"/>	+	1 A	<input type="checkbox"/>	00 blue	30* ultra blue	50* metal dark blue
Switch	Mounting	L 6 low temp.		Cap	02 green	40* dusty blue	53* metal light grey	
	T through-hole	H 9 high temp.			03* grey	42* aqua blue	57* metal dark grey	
	S surface mount			1 Z A	04 yellow	32 mint green	58* metal bordeaux	
				Cap	06* white	33 tele grey		
					08 red	34 melon		
					09* black	38 noble red		*) Colours for 1ZA

3 A	<input type="checkbox"/>	<input type="checkbox"/>	+	1 M	<input type="checkbox"/>	00 blue	
Switch	Mounting	L 6 low temp.		Cap	02 green		
	T through-hole	H 9 high temp.			03 grey		
	S surface mount				04 yellow		
					06 white		
					08 red		
					09 black		

3 A	T	<input type="checkbox"/>	+	1 H	<input type="checkbox"/>	00 blue	Lens
Switch	Mounting	L 6 low temp.		LED	02 green	01 transparent	
	T through-hole	H 9 high temp.		00 blue	03 green	2 green	
				20 green	04 yellow	4 yellow	
				40 yellow	06 white	6 frosted white	
				80 red	08 red	8 red	
					09 black		

Ordering example: 3ATL680 + 1H098

For updates of products and/or changes of specifications please see www.mec.dk