



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X,X=±0.4
X,XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. CONTACT RATINGS: 25mA @24VDC.
 5. MATERIAL (TERMINALS/CONTACTS):
PHOSPHOR BRONZE w/GOLD PLATE OVER
NICKEL PLATE
 6. INSULATION RESISTANCE:
100MEGA-OHMS MIN @500VDC
 7. CONTACT RESISTANCE (INITIAL):
50MILLI-OHMS @2-4VDC @100mA
 8. OPERATING FORCE: 1000GF MAX.
 9. TRAVEL: 2MM TYPICAL
 10. PACKAGED: DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.
 11. TOP TAPE SEAL FOR FLUX WASH
 12. ▲ DENOTES CRITICAL PARAMETER.

A		13310	RELEASED FOR PRODUCTION	7/23/03	AR	TITLE		
REV.	ECN No.		DESCRIPTION	DATE	CHKD	SCALE	2:1	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED							DATE	7/23/03
							DR	AR
							DWG	N321061
							REV	A
							KAS2106ET	
							E-SWITCH®	