



Graphic Series Keypads



Tough keypads with 'snap-on' keytops for custom graphics

- Rugged, reliable and responsive data entry
- Available with optional integrated LED illumination of keytops and keytop characters
- Keytop colours and graphics can be configured to suit almost any application
- Sealed against water and dust to IP54 specification
- 4, 12 and 16 key formats
- Can be fixed to a flat surface or under panel mounted for a flush, low profile installation
- Extensive library of keytop graphics and colour tiles available
- Custom keytop graphics can be created and fitted 'on-site'



www.storm-interface.com




Storm Interface products include technology protected by international patents and design registration. All rights reserved.

storm

K Range Graphic Series Keypads

STORM Graphic Series Keypads feature keytop legends that can be configured or customised without dismantling the keypad. The unique 'snap on' keytop cover encapsulates a polymer legend tile. The legend tiles can be selected from an extensive library of standard characters or symbols to suit many applications. Alternatively custom keytop graphics can be created using laser printed acetate film or screen printed polymer film. Keytop colours can also be customised by backing the transparent legend film with a second, coloured tile. When pressed into place the impact resistant keypad provides a permanent tamper resistant lens. The keypad cover protects the encapsulated legends from wear, physical damage, water ingress and unauthorised removal. These field proven keypads are ideal for use in a wide range of industrial and commercial applications. Also available with optional integrated LED illumination of keytops and keytop graphics, making these keypads suitable for use in dark or subdued lighting conditions.

Overall Dimensions



Connection Details for 4 Key Keypad

CONTACT CONNECTIONS
5 4 3 2 1
(As viewed from rear of keypad)

A 1
B 2
C 3
D 4

KEY LOCATION
(As viewed from front of keypad)

CONN. PIN	ROW/COLUMN
1	common
2	D
3	C
4	B
5	A

Connection Details for 12 Key Keypad

CONTACT CONNECTIONS
8 7 6 5 4 3 2 1
(As viewed from rear of keypad)

A 1 2 3
B 4 5 6
C 7 8
D 9 10

KEY LOCATION
(As viewed from front of keypad)

CONN. PIN	ROW/COLUMN
1	A
2	B
3	1
4	2
5	3
6	-
7	D
8	C

Connection Details for 16 Key Keypad




CONTACT CONNECTIONS
8 7 6 5 4 3 2 1
(As viewed from rear of keypad)

A 1 2 3 4
B 5 6 7 8
C 9 10 11 12
D 13 14 15 16

KEY LOCATION
(As viewed from front of keypad)

CONN. PIN	ROW/COLUMN
1	A
2	B
3	1
4	2
5	3
6	4
7	D
8	C

Mounting & Connection Details



All dimensions are in mm

Electrical

Contact Bounce	5ms (max)
Contact Resistance	100 ohms (max)
Insulation Resistance	50 Mohms (min)
Breakdown Voltage	500V AC (max 60 secs.)
Operating Voltage	24V DC (max)
Operating Current	50mA (max)

Mechanical

Operational Life	2 million cycles (min) per key
Keytop Travel	1.4mm nominal
Actuation Force	180gms nominal
Connector	0.1" pitch, gold plated square pin, male connector

Environmental

Water / Dust Sealed

Operational Temperature

IP54 (when mounted to suitable enclosure)
-20°C to +60°C (Dry)

Material

Casing

Keytops

Contact Circuit

General Service Polymer
(black or mid grey)

General Service Polymer
(transparent)

Gold on Nickel plated FR4

Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.



FM 39602

For details of available STORM Graphic Series keytop character sets, please request the legend tile character library, document ref. GFX-LEG1-01

Designed & produced by
NIK Design
www.nikdesign.co.uk

GFX-LIT-01 Rev 4
Nov 2008



Storm is a trademark of Keymat Technology Ltd
Storm Interface is a trading name of Keymat Technology Ltd

Storm Interface products include technology protected by international patents and design registration. All rights reserved.