



RECOMMENDED PANEL MOUNTING




4PST CONTACT CONFIGURATION



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
 - ▲3. RATINGS: 250VAC @ 5 AMPS, 24VDC @ 6A
 4. ELECTRICAL LIFE: 50,000 MAKE AND BREAK CYCLES.
 5. OPERATION TEMP: -25°C TO +55°C
 - ▲6. LAMP VOLTAGE: 6V AC/DC INCANDESCENT 200mA
 7. PACKAGE: BOX/20 PIECES PER
 8. ▲DENOTES CRITICAL PARAMETER.
 9. 2002/95/EC (ROHS) COMPLIANT

PARTS LIST

Item	Qty.	Dwg. No.	Part No.
1	1	F051702	25mm RING FOR LA SERIES
2	1	F060605	LASEEV140
3	1	F060253	25mm WHT LENS
-	1	F050402	50-004-02 (LAMP)



REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	16926	RELEASED FOR PRODUCTION	1/26/07	TN

TITLE				
LASEEV14A WHT				
SCALE	DATE	DR	DWG	REV
1:1	1/26/07	TN	XF0710P	A

