Compact Push Type Power Switches

Malaysia

Series: **R2**

Type: **ESB92D**

High reliability type (applicable to practical rates of usage)




■ Features

- Available for both DPST and SPST Available for equipment subject to inrush current (128 A)
- Special heat resistant structure
- Meets the world\(\blacktriangle \) major safety standards
- Rapid switching structure, applicable to IEC60065 6th edition (Refer to the notes.)
- Cadmium-free contact

■ Recommended Applications

- AV Equipment: TVs and audio systems
- OA Equipment: PCs, monitors, printers, etc.

■ Explanation of Part Numbers



■ Specifications

| Rating | TV-5, 5 A 250 Vac (UL, CSA) 4 A/128 A 250 Vac (European standards) | | |
|-------------------------------|---|-------------|-------------|
| Safety Standards | UL, CSA, VDE, BEAB, SEMKO, FIMKO, SEV, DEMKO, NEMKO | | |
| Circuit Diagram | DPST | | |
| Operating Force | Circuit | Lock Travel | |
| | | 1.5 mm | 2.5 mm |
| | DPST | 8.0 N±3.0 N | 8.0 N±3.0 N |
| Travel | Lock Travel: 2.5 mm, Full Travel: 3.5 mm | | |
| | Lock Travel: 1.5 mm, Full Travel: 2.5 mm | | |
| Minimum Quantity/Packing Unit | 25 pcs. Polyethylene Bag (Bulk) | | |
| Quantity/Carton | 300 pcs. | | |

* OA equipment: PCs, monitors, printers, etc.

■ Dimensions in mm (not to scale)

