



SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	NONE	DN
2-3	OPEN	2-1

RECOMMENDED PCB LAYOUT



CIRCUIT: SPST



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. RATING: 5A @120VAC OR 28VDC 2A @250VAC
  - ▲5. MATERIAL: FIXED TERMINAL & MOVING CONTACT  
Copper Alloy w/Silver Plate
  6. CONTACT RESISTANCE: 10mILLI Ohms max initial @2-4VDC, 100mA for AG & AU
  7. ELECTRICAL LIFE: 30,000 make-and-break cycles at full load.
  8. INSULATION RESISTANCE: 1,000M ohm min.
  9. DIELECTRIC STRENGTH: 1000V RMS @sea level
  10. OPERATING TEMP.: -30°C to 85°C
  11. ▲DENOTES MAJOR DIMENSIONS.
  12. 2002/95/EC (ROHS) COMPLIANT

REV.	ECN No.	DESCRIPTION	DATE	CHKD
C	16904	UPDATED NOTES, FIXED IN QAD	1/22/07	TN
B	15158	CHANGED DIMENSION	8/9/05	PV
A	11605	RELEASED FOR PRODUCTION		

SCALE	DATE	DR	DWG	REV
2:1	1/22/2007	TN	T301026	C



300AWSP1JIBLKM6QE