



NOTE:

1. ALL DIMENSIONS IN MM [INCH].
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT MATERIAL: GOLD FLASHING OVER SILVER PLATE OVER COPPER ALLOY
5. CONTACT RATING: 0.3A @125VAC
6. OPERATING FORCE: 800±200 GRAMS
7. OPERATING TEMP: -30°C TO 85°C
- ▲ 8. CIRCUIT SP: 12 POSITION 30° INDEX.
9. DIELECTRIC STRENGTH: 500VAC- 60 SEC.
- ▲ 10. HARDWARE SUPPLIED ON SWITCH:
LOCKWASHER, HEXNUT
11. ▲ DENOTES CRITICAL PARAMETER.

E-SWITCH®

TITLE KC52A9.501NPF

| | | | | |
|-----|--------|-------------------------|--------|----|
| A | 15064 | RELEASED FOR PRODUCTION | 7/8/05 | JB |
| REV | PCR NO | DESCRIPTION | DATE | BY |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

| | | | | |
|-------|----------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 1.5:1 | 7/8/2005 | JB | G511002 | A |