



CHARACTERISTICS OPERATING FORCE----- 82 GRAMS MAX RELEASE FORCE----- 8 GRAMS MIN DIFFERENTIAL TRAVEL----- .028 MAX OVERTRAVEL----- .070 MIN RELEASE TRAVEL----- .017 MIN		ELECTRICAL DATA CONTACT ARRANGEMENT S P D T L156 11A 1/3HP 125, 250 OR 277 VAC 1/2A 125 VDC, 1/4A 250 VDC 4A 125 VAC "L"		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: <input checked="" type="checkbox"/> US (INCH) CUSTOMARY <input type="checkbox"/> SI (MM) METRIC NO PLACE X ±.040 ±1 ONE PLACE .X ±.030 ±0.4 TWO PLACE .XX ±.015 ±0.15 THREE PLACE .XXX ±.005 ± ANGLES ± ± RAW MATERIAL-COMMERCIAL STANDARD		DRAWN DCS 18 JAN 01 CHECK SAV 18 JAN 01		Honeywell Sensing and Control TITLE SWITCH - BASIC	
		THIRD ANGLE PROJECTION 		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL SENSING AND CONTROL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL. DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED		SIZE DWG TYPE DRAWING NAME REV B M V7-1B19D8-022 2			
				PTC 2D ASME Y14.5M-1994		SCALE 2:1 WEIGHT SHEET 1 OF 1			