


FO-55111-A

HONEYWELL
PART NUMBER
311SM702-T
PRODUCT CODE
TZA2682

REV	DOCUMENT	CHANGED BY	CHECK
9	0038445	SSK 21APR08	BLR



NOTES
 ▲ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .087 MAX DIA ON .375 ± .002 CENTERS
 2- SWITCH WILL WITHSTAND TEMPERATURE OF 250°F
 3- TERMINALS ARE PLATED FOR SOLDERING

RELEASE NO. PR -1354
 REPLACES -

CHARACTERISTICS
OPERATING FORCE -- 12 GRAM MAX
RELEASE FORCE --- 2 GRAM MIN
DIFFERENTIAL TRAVEL - - .015 MAX
OVERTRAVEL - - - .026 MIN

ELECTRICAL DATA	
CONTACT ARRANGEMENT S P D T	
30 VOLTS DC RATING	
INDUCTIVE	SEA LEVEL 50,000 FT
RESISTIVE	3 AMP 2.5 AMP
	5 AMP 5 AMP
MAXIMUM INRUSH 24 AMP	
UL, CSA	4A, 250 VAC
	BRAND L119

DESIGN UNITS: INCH	
TOLERANCES UNLESS NOTED:	
NO PLACE	.X ±
ONE PLACE	.XX ±
TWO PLACE	.XXX ±
THREE PLACE	.XXXX ±
FOUR PLACE	.XXXX ±
ANGLES	±
THIRD ANGLE PROJECTION	

DRAWN	VK	21FEB 08
CHECK	RJ	21FEB 08
THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		
INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY		
RASTER		

Honeywell			
TITLE SWITCH - BASIC			
SIZE	TYPE	DRAWING NAME	REV
B	I	311SM702-T	9
SCALE	-	WEIGHT .006 LB MAX	SHEET 1 OF 1

4

3

2

1