


- NOTES**
- 1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX. DIA ON 1.000±.002 CENTERS
 - 2 - SUITABLE ONLY FOR APPLICATIONS IMPARTING A RAPID STROKE TO THE SWITCH PLUNGER

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



CHARACTERISTICS	OPERATING FORCE - - - - - 26- 38 OZ	ELECTRICAL DATA	SCALE FULL			
	RELEASE FORCE - - - - - 10 OZ MIN		CONTACT ARRANGEMENT SEE CIRCUIT DIAGRAM		DO NOT SCALE PRINT	
	DIFFERENTIAL TRAVEL - - - .007 - .015	30 VOLTS DC RATING (SEA LEVEL TO 50,000 FT) INDUCTIVE - - - - - 25 AMP RESISTIVE - - - - - 30 AMP MAXIMUM INRUSH - - - - - 75 AMP BASED ON LIFE OF 25,000 OPERATIONS	TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±			
	OVERTRAVEL - - - - - .010 MIN		25A 125, 250, OR 480 VAC L58 3/4 HP 125 VAC, 1 1/2 HP 250 VAC 1A 125 VDC, 0.5A 250 VDC	DIM. mm TOL. mm/in	DIM. in TOL. mm/in	NO PLACES X 1/.04 ONE PLACE X,X 0.4/.016 TWO PLACES X,XX 0.15/.008 THREE PLACES X,XXX ANGLES
		DESIGN UNITS <input type="checkbox"/> SI METRIC <input checked="" type="checkbox"/> US CUSTOMARY		WEIGHT .067 LB		

BA-3ST
 PAGE 1 OF 1

M
 DRAWING NUMBER

ISSUE 11

REVISIONS

A	CO	53551
S	L	B
15 SEPT 83		
B	0063005	
J	A	P
5 APR 88		
C	CO	59351-D
J	W	B
18 JUL 91		
D	205503	
G	J	W
1 MAY 02		

FO-52848-A
 DRAWN
 S L B 15 SEPT 83 CHECK
 S L B 15 SEPT 83 CHECK
 S L B 15 SEPT 83 CHECK