MICRO SWITCH
FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 01929

SWITCH – ENCLOSED

CATALOG LISTING
201LS1



CIRCUIT DIAGRAM







CAM TRACKING VIEW



NOTES
1 - SWITCH IS ASSEMBLED FOR ACTUATION IN BOTH DIRECTIONS BUT MAY BE ADJUSTED TO ACTUATE IN EITHER THE CLOCKWISE DIRECTION ONLY OR THE COUNTERCLOCKWISE DIRECTION ONLY
2 - TO CONVERT SWITCH FOR ACTUATION IN EITHER THE CLOCKWISE OR COUNTERCLOCKWISE DIRECTION ONLY, REMOVE ACTUATOR HEAD AND ROTATE THE NOTCHED PLUNGER 90° TO THE RIGHT FOR CLOCKWISE ACTUATION OR 90° TO THE LEFT FOR COUNTERCLOCKWISE ACTUATION
3 ROLLER LEVER MAY BE LOCKED IN ANY POSITION THRU 360°
4 - LEVER FURNISHED UNASSEMBLED IN UNIT PACKING BOX

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	
OPERATING TORQUE	4.5 IN-LB MAX
FULL OVERTRAVEL TORQUE	6 IN-LB MAX
RELEASE TORQUE	.75 IN-LB MIN
PRETRAVEL	20° MAX
DIFFERENTIAL TRAVEL	12° MAX
OVERTRAVEL	30° MIN
RELEASE TRAVEL	4° MIN
SWITCH-BASIC REPLACEMENT	2MN6

ELECTRICAL DATA

CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)

10A-120, 240, OR 480 VAC, 1/3 HP - 120 VAC
3/4 HP - 240 VAC; 0.8A - 115 VDC; 0.4A - 230 VDC
.1A - 550 VDC
PILOT DUTY: 600 VAC MAX

SCALE 1/2 TO 1

DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
ONE PLACE (.0) ±.030
TWO PLACE (.00) ±.010
THREE PLACE (.000) ±.005
ANGLES ±2°

WEIGHT

CATALOG LISTING 201LS1 PAGE 1 OF 1
DRAWING NUMBER M
RELEASE NO.
ISSUE 15
REPLACES
CHECK
REVISIONS
A ECO-96-463-B DLT 7 SEP 99
B ECO-200178 AS 5 APR 00
DRAWN OMW 19 MAR 64
CHECK DAW 2.9 MAR 64
CHECK
CHECK
FORMTEK
FO-00378-003

Downloaded from Elcodis.com electronic components distributor