



MICRO SWITCH
a Honeywell Division

SWITCH - ENCLOSED

CATALOG LISTING
BZE6-2RN80

FED. MFG. CODE 91225

CATALOG LISTING
BZE6-2RN80

ISSUE
M
11

REPLACES

CHECK

REVISIONS

A	10/25/88	REVISED
B	10/25/88	REVISED
C	10/25/88	REVISED
D	10/25/88	REVISED

DDM/CAD
DRAWN

SAV 15 OCT 92
CHECK

BP 22NOV05
CHECK

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CHARACTERISTICS	
OPERATING FORCE	9-24 OZ
RELEASE FORCE	4 OZ MIN
DIFFERENTIAL TRAVEL	.0004-.0020
OVERTRAVEL	.219 MIN
BASIC SWITCH REPLACEMENT	BZ-2RN784

ELECTRICAL DATA	
CONTACT ARRANGEMENT S P D T	
L74	15A 125, 250 OR 480 VAC 2A 600 VAC 1/8HP 125 VAC, 1/4HP 250 VAC 1/2A 125 VDC, 1/4A 250 VDC
CE 1.5A, 240Vac	

THIRD ANGLE PROJECTION	
SCALE	FULL
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.01) ±.030
TWO PLACE	(.00) ±.015
THREE PLACE	(.000) ±.005
ANGLES	±
WEIGHT	.56 LB APPROX

NOTE

△1 FURNISHED UNASSEMBLED

2 - 3X 6-32 UNC X (.219) BINDING HEAD TERMINAL SCREW AND CUPWASHER

3 - SEAL RATING: NEMA1,3
IP54

ANSI Y14.5M-1982 APPLIES