

FORMTEK
DRAWN
G/JW 11 MAY 95
CHECK
JJA 25 MAY 95
REVISIONS
A 25 MAY 95
1 25 MAY 95
ISSUE
15
CATALOG LISTING
BAFI-2RN18-LH
PAGE 1 OF 1
RELEASE NO. SR-5195
REPLACES ISSUE 12203
SKETCH 1

MICRO SWITCH
a Honeywell Division
FED. MFG. CODE 91923

SWITCH-ENCLOSED

CATALOG LISTING
BAFI-2RN18-LH
(LEFT HAND)

.56
1.3
1.030
.53
1.030
98
ACROSS
FLATS
GASKET TYPE SEAL BETWEEN
COVER AND HOUSING.
1.25 MAX. OPERATING POSITION.
SWITCH WILL OPERATE BY MOVING ACTUATOR
IN ANY DIRECTION EXCEPT DIRECT PULL.
4) 8-32UNC X .562 REF PAN
HEAD SCREW AND WASHER (SENSITAINED)
1.25 ± .030
280 MAX.
6.235 ± .100
ELASTOMER PLUNGER SEAL SECURED TO
COMPONENTS BY EXTERNAL BANDING.
HEX SEAL NUT, .938 REF ACROSS FLATS.
25 R
1.08
.25 R
1.08
1.010
.812
59 DIA.
1.625
1.422 REF
3.250 ± .010
4.0
1.31265 DIA. HOLE.

NOTE
1 - 8-32 UNC X (.219) BINDER HEAD, COMBINATION, TERMINAL SCREWS
AND CUP WASHERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CHARACTERISTICS	ELECTRICAL DATA	THIRD ANGLE PROJECTION
OPERATING POSITION --- 15° MAX.	CONTACT ARRANGEMENT S. P. D. T.	SCALE FULL
BASIC SWITCH REPLACEMENT --- BA-2R708-P7	BREAK DISTANCE .020 MIN	DO NOT SCALE PRINT
	L23 20A 125, 250 OR 480 VAC 10A 125 VAC "L" 1HP 125 VAC, 2HP 250 VAC 1/2A 125 VDC, 1/4A 250 VDC	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
		ONE PLACE 1.01 ± .030 TWO PLACE 1.001 ± .015 THREE PLACE 1.0001 ± .005 ANGLES ±
		WEIGHT