

4





3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
AD	OO	F LTR	DESCRIPTION	DATE	OWN	APP'D
		A	ECO-07-001263	13FEB2007	RB	MS



P.C. HOLE LAYOUT
 TOLERANCE ±.002,
 UNLESS OTHERWISE NOTED

CIRCUIT DIAGRAM
 NOTE: TERMINAL NUMBERS
 ARE FOR REFERENCE ONLY
 AND DO NOT APPEAR ON
 SWITCHES.

SPECIFICATIONS:

Materials:
 Case, Nylon 66, UL94HB, Natural finish
 Cover, Stainless Steel
 Actuator, PBT UL94HB, Black
 Moving contact, Copper Alloy, Silver finish
 Fixed contact/Terminal, Copper Alloy, Silver over Nickel finish

Electrical:
 Max Contact Rating, 50mA@ 24V DC, Per EIA-448, Method 6
 Min Contact Rating, 10microamp@1V DC
 Initial Contact resistance, 50 milliohms max, Per EIA-364-23B, each position
 Insulation Resistance, 1000 Megohm min. Per EIA-364-21C each position
 Dielectric strength, 500 V AC for 1 minute, Per EIA-364-20B, Condition 1, each position.
 Life Expectancy, 100,000 cycles

Mechanical:
 Actuation force, SEE P/N TABLE
 Actuation Travel, .25 +.20/- .10 mm
 Life Expectancy, 100,000 cycles min (2 cycles per second and 150% actuation force),
 Per EIA-448 Methods 8 and 9
 Vibration, Per EIA 364-28D, Condition VII, Level E
 Mechanical Shock, Per EIA-364-27C, Condition A

Environmental:
 Operating Temperature, -35 to +85 degrees C, Per EIA-448, Method 10
 Storage Temperature, -35 to +85 degrees C
 Humidity and Temperature Cycling Per EIA-364-31B, Method III
 Thermal Shock, Per EIA-364-32C, -35 to +85 degrees C
 Solderability, Per EIA-364-52, Class 2, Category 1, Temp, 245 degrees C max,
 Time, 2.5 seconds max, 95% Minimum coverage
 Resistance to Solder Heat, Per 109-202, Condition B
 1. No change in initial electrical and mechanical characteristics

NOTES:

1. ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003(ROHS).

100,000	130±50gf	FSMCH	1825966-1
LIFE CYCLE	ACTUATION FORCE	ALCO PART NUMBER	TYCO PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DRN R. BROWN 13FEB2007	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS mm [INCHES]		CHK M. SARVER 13FEB2007	APPC M. SARVER 13FEB2007	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME TACT SWITCH, 3.5 x 6.0 x 4.3 mm, HIGH TEMP, FSMCH		
0 PLG ± .010 1 PLG ± .012 2 PLG ± .015 3 PLG ± .020 4 PLG ± .025 ANGLES ± .010		APPLICATION SPEC	SIZE A2	CAGE CODE 00779
MATERIAL SEE SPECIFICATIONS		PRODUCT SPEC	DRAWING NO C=1825966	RESTRICTED TO -
FINISH SEE SPECIFICATIONS		WEIGHT	SCALE 5:1	SHEET 1 of 1
		CUSTOMER DRAWING	REV A	