



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 12VDC, 50mA
 - ▲5. OPERATING FORCE: 180 ± 50 gms
 6. TRAVEL: 0.3mm ±0.1
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
 - ▲9. PACKAGE: TAPE AND REEL - 3000 PIECES PER REEL
 10. ▲ DENOTES CRITICAL PARAMETER
 12. 2002/95/EC (ROHS) COMPLIANT.

E-SWITCH®

B	16590	UPDATED NOTES, DIAGRAMS	10/26/2006	TN	TITLE TL1014BF180QG				
A	14789	RELEASED FOR PRODUCTION	3/24/05	AR					
REV	PCR NO	DESCRIPTION	DATE	BY	SCALE	DATE	DR	DWG	REV
<small>THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED</small>					8:1	3/25/2005	AR	D400000	B