



SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	OFF	DN
2-3, 5-6	OPEN	2-1, 5-4
8-9		8-7

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4, X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 5A @120VAC OR @28VDC; 2A @250VAC
 5. ELECTRIC LIFE: 50,000 MAKE AND BREAK AT FULL LOAD.
 6. INSUL. RESISTANCE: 1,000M-OHMS MIN
 7. DIELECTRIC STRENGTH: 1,000V RMS @SEA LEVEL
 8. OPERATING TEMP.: -30°C TO +85°C

E-SWITCH®

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	11093	RELEASED FOR PRODUCTION	12/06/00	PML

TITLE	SCALE	DATE	DR	DWG	REV
100 3P-3 T2 B9 M7 Q E	2:1	12/06/00	PML	T135012	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED