LT-Series Toggle Switches

The LT-Series illuminated toggle switches feature a three-color lighting sequence from a single lamp. These lighted toggles contain neoprene bushing seals for dust and moisture protection and provide a simple way to dress-up most any Marine or Transportation industry panel. A variety of circuits and terminations are available.

Dielectric Strength
1000V-live to dead metal parts
Electrical Life
50,000 cycles- maintained
25,000 cycles- momentary
Mechanical Life
100,000 cycles
Operating Temperature
32°F to 185°F (0°C to 85°C)



LT-1561 - 1 30 - 012

1 Base Part Number — 2 Actuator Style — 3 Lighting Sequence — 4 Lamp Voltage

1 BASE PART NUMBER: SERIES/POLES/ILLUMINATION/CIRCUITRY[3]/RATING/TERMINATION[5]

10A 250VAC, 15A 125VAC, 3/4 HP 125-250VAC, 15A 15-28VDC

Single Pole in Double Pole base					*Double Pole*			
solder lug	*.250 tab*	*screw term.*	*wire leads*		*solder lug*	*.250 tab*	*screw term.*	*wire leads*
LT-1510	**LT-1511**	**LT-1514**	**LT-1515**	ON-NONE-OFF	**LT-2510**	**LT-2511**	**LT-2514**	**LT-2515**
LT-1520	**LT-1521**	**LT-1524**	**LT-1525**	ON-NONE-(OFF)	**LT-2520**	**LT-2521**	**LT-2524**	**LT-2525**
LT-1530	**LT-1531**	**LT-1534**	**LT-1535**	(ON)-NONE-OFF	**LT-2530**	**LT-2531**	**LT-2534**	**LT-2535**
LT-1540	**LT-1541**	**LT-1544**	**LT-1545**	ON-NONE-ON	**LT-2540**	**LT-2541**	**LT-2544**	**LT-2545**
LT-1550	**LT-1551**	**LT-1554**	**LT-1555**	ON-NONE-(ON)	**LT-2550**	**LT-2551**	**LT-2554**	**LT-2555**
LT-1560	**LT-1561**	**LT-1564**	**LT-1565**	ON-OFF-ON	**LT-2560**	**LT-2561**	**LT-2564**	**LT-2565**
LT-1570	**LT-1571**	**LT-1574**	**LT-1575**	ON--OFF-(ON)	**LT-2570**	**LT-2571**	**LT-2574**	**LT-2575**
LT-1580	**LT-1581**	**LT-1584**	**LT-1585**	(ON)-OFF-(ON)	**LT-2580**	**LT-2581**	**LT-2584**	**LT-2585**

2 ACTUATOR STYLE

paddle [1]

1 clear paddle
4 solid color paddle

snapkap style [2]

5 bright chrome
6 satin chrome
7 black molded

3 LIGHTING SEQUENCE[3,4]

	position 1	*position 2*	*position 3*
01	red	red	red
02	amber	amber	amber
03	green	green	green
10	red	---	none
11	red	clear	red
12	red	clear	amber
13	red	clear	green
14	red	clear	blue
15	red	clear	clear
20	amber	---	none
21	amber	clear	red
22	amber	clear	amber
23	amber	clear	green
24	amber	clear	blue
25	amber	clear	clear
30	green	---	none
31	green	clear	red
32	green	clear	amber
33	green	clear	green
34	green	clear	blue
35	green	clear	clear
40	blue	---	none
41	blue	clear	red
42	blue	clear	amber
43	blue	clear	green
44	blue	clear	blue
45	blue	clear	clear
50	clear	---	none
51	clear	clear	red
52	clear	clear	amber
53	clear	clear	green
54	clear	clear	blue
55	clear	clear	clear

4 LAMP VOLTAGE[4]

neon
125 125 volts neon
250 250 volts

incandescent
006 6 volts
012 12 volts
018 18 volts
024 24 volts

NOTES
1 Solid color paddle available with lighting sequence 01, 02, 10 or 20.
2 SnapKap Toggle Lenses are available separately. Consult factory.
3 Independent lamp is standard. Dependent lamp with ON-OFF function (including momentary) is available with Lighting Sequences 10, 20, 30, 40 and 50. (No light in OFF position.)
4 Green and blue not recommended with 125 volt or 250 volt neon lamps.
5 Additional terminations available. Consult factory for details.
( ) Indicates momentary function.

Downloaded from Elcodis.com electronic components distributor