

Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant

260 Hudson River Rd Waterford NY 12188

Revised: 03/28/2008

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS

CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1

NFPA

Flammability: 1 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Irritating to eyes, respiratory system and skin. May be harmful if swallowed. Adverse liver and reproductive effects reported in animals. Attention: Not for injection into humans.

Form: Solid Color: Translucent Odor: SLIGHT AMMONIA

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed.

SKIN

May cause mild skin irritation.

INHALATION

Causes mild respiratory tract irritation. Applies in uncured state.

EYES

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

May cause liver effects.; Reproductive hazard.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.



Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

ROUTES OF EXPOSURE

Dermal; Eyes

3. COMPOSITION / INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS REG NO.	<u>WGT. %</u>	
A. HAZARDOUS			
Octamethylcyclotetrasiloxane	556-67-2	1 - 5 %	
Hexamethyldisilazane	999-97-3	1 - 5 %	
Methyltrimethoxysilane	1185-55-3	1 - 5 %	
B. NON-HAZARDOUS Siloxanes & Silicones, Dimethylpolymers	68554-67-6	10 - 30 %	
w/Methylsilsesquioxanes Treated Fumed Silica	68583-49-3	10 - 30 %	
Polydimethylsiloxane	63148-62-9	10 - 30 %	
Treated Filler	60842-32-2	10 - 30 %	
Methoxypolydimethylsiloxane	68037-58-1	60 - 90 %	

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Material Safety Data Sheet

Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT: ca. 110 °C; 230 °F

METHOD: Pensky-Martens closed cup ASTM D 93

FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Increase area ventilation.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Product releases methanol during application and curing. Product releases ammonia during application and curing. Use mechanical ventilation to stay below TLV of 25 ppm ammonia. Avoid contact with skin and eyes. Use only in well-ventilated areas. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Keep away from children.

STORAGE

Store away from heat, sources of ignition, and incompatibles. Keep container closed.

Material Safety Data Sheet

Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers; Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Impermeable or chemical resistant gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	<u>Value</u>
Octamethylcyclotetras iloxane	556-67-2	Z_INTL_OEL, REL	5 ppm

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:

FREEZING POINT:

MELTING POINT:

Not applicable

Not applicable

PHYSICAL STATE: Solid

ODOR: SLIGHT AMMONIA

COLOR: Translucent

EVAPORATION RATE (BUTYL ACETATE=1): < 1
SPECIFIC GRAVITY (WATER=1): ca. 1.035
DENSITY: ca. 1.035 g/cm3

VOLATILE ORGANIC CONTENT (VOL): 2.2 %(m) SOLUBILITY IN WATER (20 C): Insoluble

Page 4/8

Material Safety Data Sheet

Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

SOLUBILITY IN ORGANIC SOLVENT (STATE

PARTIAL IN TOLUENE

SOLVENT):

VOC EXCL. H2O & EXEMPTS (G/L): ca. 33

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO2); Carbon monoxide; Formaldehyde; Silicon dioxide.; Oxides of nitrogen.; Methanol; Ammonia; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

Octamethylcyclotetrasiloxane Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size). Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liver weights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utililizing laboratory rabbits and guinea pigs

Material Safety Data Sheet

Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents. Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found. Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300 ppm dosing levels. Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group. The relevance of these data to humans is unclear. Further studies are ongoing. In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study., Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SENSITIZATION

No data available

SKIN IRRITATION

No data available

EYE IRRITATION

No data available

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available

DISTRIBUTION

No data available

CHEMICAL FATE

No data available



Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information: This product is not regarded as dangerous goods according to the

national and international regulations on the transport of dangerous

goods.

15. REGULATORY INFORMATION

<u>Inventories</u>

TSCA list y (Positive listing)
Canada DSL Inventory y (Positive listing)
Korea Existing Chemicals y (Positive listing)

Inventory (KECI)

China Inventory of Existing y (Positive listing)

Chemical Substances

Australia Inventory of Chemical y (Positive listing)

Substances (AICS)

Philippines Inventory of y (Positive listing)

Chemicals and Chemical Substances (PICCS)

EU list of existing chemical y (Positive listing)

substances

Canada NDSL Inventory n (Negative listing)
Japan Inventory of Existing & n (Negative listing)

New Chemical Substances

(ENCS)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

CALIFORNIA PROPOSITION 65

WARNING! This product contains a chemical known in the State of California to cause cancer. 108-88-3, Toluene.



Version: 1.6 03/28/2008

RTV6708 12C-Crtrg (0.738LBS-0.335KG) POLYSILOXANE SEALANT (translucent)

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS: 3214.10.00.10 Mastic based on rubber

ECCN: EAR99

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = MST = mist NT = not tested STEL = short term exposure limit ppm = recommended ppb = parts per billion By-product= reaction by-product, TSCA inventory status parts per million not required under 40 CFR part 720.30(h-2).