

RTV Silicones by MOMENTIVE performance materials

2-Part Potting/Encapsulating Compound

RTV60



Technical Support
for RTV Silicones

 1-800-255-8886



ALL MG PRODUCTS ▾

▶ STOCKED ITEM

▶ BUY NOW

Jump to Product Number



- [Accessories](#)
- [Adhesives](#)
- [Brushes](#)
- [Cleaners / Degreasers](#)
- [Contact Cleaners](#)
- [Desoldering Braid](#)
- [Dusters & Circuit Coolers](#)
- [EMI / RFI Shielding](#)
- [Epoxyes](#)
- [Flux and Flux Remover](#)
- [Glass & Screen Cleaners](#)
- [Isopropyl Alcohol](#)
- [Lead Free Solder](#)
- [Lubricants](#)
- [Potting & Encapsulating](#)
- [Protective Coatings](#)
- [Pens](#)
- [Prototyping Materials](#)
- [RTV Silicones](#)
- [Soldering/desoldering](#)
- [Specialized Cleaners](#)
- [Swabs](#)
- [Thermal Management](#)
- [Thermally Conductive Adhesives](#)
- [Wipes](#)

Primary Characteristics

- ▶ Red flowable
- ▶ **Extreme high temp.**
- ▶ [Condensation cure](#)
- ▶ Useful to 260°C (500°F)
- ▶ Thermal insulator
- ▶ [Primer](#) required

Use for:

- ▶ Aerospace applications such as potting, encapsulating, coating and cushioning

Excellent for potting and encapsulating electric motors and transformers. Also used for fabrication of rubber parts and casting molds for low-melting point metals. Recommended for aerospace applications and as a thermal insulator. Excellent retention of elastomeric properties at temperatures from -54°C to 260°C (-65°F to 500°F) continuously, and up to 316°C (600°F) for short periods of time. Cures at room temperature and has excellent adhesion qualities. A [silicone primer](#) is required. The product comes complete with catalyst DBT. [Specialized catalysts](#) are available upon request. RTV60 is a low viscosity version of [RTV88](#) and will flow into small areas.

Available Sizes

Catalog Number	Sizes Available	Description
RTV60-1P	1 pint	pail
RTV60-1G	▶ SPECIAL ORDER 1 gallon	pail
RTV60-5G	▶ SPECIAL ORDER 5 gallon	pail
RTV60 requires a primer. Visit our primer guide for details.		

Specifications

Use	Potting & Encapsulating
Special Feature	High Temperature
Cross Reference	RTV60
Uncured Properties	
Consistency	Flowable
Color	Red
Specific Gravity	1.48
Pot Life	2 hours
Cure Through Time	24 hours
Useful Temp. Range	-54°C to 260°C (-65°F to 500°F)
Cured Properties - MECHANICAL	
Hardness	57 (Shore A)
Tensile Strength	6.86 MPa (990 psi)
Elongation	120%










M.G. Chemicals Disclaimer for RTV Silicones >

[Locate Distributor >](#)

Quick Links

- ▶ [MSDS](#)
- ▶ [Catalyst options/MSDS](#)
- ▶ [Primer options/MSDS](#)
- ▶ [Specifications](#)
- ▶ [Available Sizes](#)

Related products:

-  [RTV21](#)
-  [RTV31](#)
-  [RTV60](#)
-  [RTV88](#)
-  [RTV560](#)
-  [RTV566](#)
-  [RTV577](#)
-  [RTV630](#)
-  [RTV656](#)

Resources

- ▶ [Selection Guide >](#)
- ▶ [One Part Chart !\[\]\(196c08192bc1688b986c9d181e52f15b_img.jpg\)](#)
- ▶ [Two Part Chart !\[\]\(482227aca45a878648135de358239c03_img.jpg\)](#)

Find by Application

- [General Purpose >](#)
- [Aerospace >](#)
- [Marine >](#)
- [High Performance Assembly >](#)
- [Electronics >](#)
- [Thermal Conductivity >](#)
- [High Temperature >](#)
- [Low Temperature >](#)



Cured Properties - ELECTRICAL	
Volume Resistivity	4.4 x 10 ¹⁴ ohm · cm
Dielectric Strength	17.7 kV/mm (450 V/mil)
Dielectric Constant	4.0 @ 1000Hz
Cured Properties - THERMAL	
Thermal Conductivity	0.31 W/m · °K
Thermal Expansion	20 x 10 ⁻⁵ cm/cm °C (11 x 10 ⁻⁵ in/in °F)
Other	
<u>Viscosity</u> (@ 25°C)	47,000 cps
Mix ratio (by weight)	100:0.5

[Return to top](#) ^