



# Temflex™ 1700 Vinyl Electrical Tape

## Data Sheet

### Product Description

Temflex™ 1700 Electrical Tape is a good quality, economical general purpose vinyl insulating tape. It has excellent resistance to: abrasion, moisture, alkalies, acid, copper corrosion and varying weather conditions (including sunlight). It is a polyvinyl chloride (PVC) tape that is flame-retardant and conformable. Temflex 1700 provides excellent mechanical protection with minimum bulk. It is a UL Listed and CSA Certified "Insulating Tape".

- UL Listed; UL 510 Standard "Insulating Tape" (product category OANZ), File E129200
- CSA Certification; Standard C22.2 No. 197-M1983 "PVC Insulating Tape", File LR 48769

### Applications

- Primary electrical insulation for all wire and cable splices rated up to 600 volts.
- Protective jacketing for high voltage cable splices and repairs.

Harnessing of wires and cables.

For indoor or outdoor applications.

For above or below grade applications.

### Typical Data/Physical Properties

#### Temperature Rating

UL 510	80°C (176°F)
CSA 22.2	80°C (176°F)

#### Flammability

UL 510	Pass
--------	------

#### Dielectric Strength\*

Standard Condition	>1000 V/mil
After Humidity Condition	>90% of Standard

#### Insulation Resistance\*

>10<sup>6</sup> Megohms

#### Thickness\*

7 mils

#### Elongation\*

200%

#### Breaking Strength\*

17 lbs/in

#### Adhesion\*

To Steel	24 oz/in
To Backing	22 oz/in

\*ASTM D1000

*Note: These are typical properties and should not be used for specification purposes.*

### Installation Techniques

The tape shall be applied in half-lapped layers with sufficient tension to conform and produce a uniform covering. In most applications, this tension will reduce the tape's width to approximately 5/8 of its original width. On pigtail splices, the tape should be wrapped beyond the end of the wires and then folded back, leaving a protective cushion to resist cut-through. Always wrap the tape "uphill". **Apply the tape with no tension on the last wrap to prevent flagging.**

### Shelf Life

Temflex 1700 Electrical Tape has a 5 year shelf-life (from date of manufacture) when stored under the following recommended storage conditions. Store behind present stock in a clean dry place at a temperature of 70°F and 40-50% relative humidity. Good stock rotation is recommended.

### Availability

Temflex 1700 Electrical Tape is available from your local 3M authorized electrical distributor in the following standard roll size:

3/4 in. x 60 ft.

Other lengths and widths available by special order.

**Temflex 1700P Printed Tape is available in two roll sizes. 3/4 in. x 66 ft. and 1 1/2 in. x 44 ft., for use in MSHA-approved (Mine Safety and Health Administration) splicing kits.**

**Important Notice:**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

**SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF THE SELLER'S PRODUCTS.**



**Electrical Products Division**

6801 Riverplace Blvd.  
Austin, Texas 78726-9000



*Recycled paper  
40% pre-consumer  
10% post-consumer*

Litho in USA

©1996 3M

80-6108-5111-7