



- △ MATERIAL:  
 HERMAPHRODITIC BACKSHELL: STEEL.  
 JACKSCREW: STEEL.  
 JACKSCREW HEAD: ABS MOLDING COMPOUND, COLOR BLACK.  
 HERMAPHRODITIC JACKSCREW COVER: UL 94V-0 RATED ABS MOLDING COMPOUND, COLOR BLACK.
- △ PLATING:  
 HERMAPHRODITIC BACKSHELL- 5µm MIN BRIGHT NICKEL OVER  
 2.5µm MIN COPPER.  
 JACKSCREW - BLUE TRIVALENT CHROMIUM OVER ZINC.
- △ RECOMMENDED WIRE: 30 AWG WITH A 0.56-0.64 INSULATION DIAMETER.  
 WIRE MUST BE APPROVED BY AMP ENGINEERING.
- 4. BULK PACKAGED 100 KITS PER BAG.

5787191-1  
 PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	10/05/01	BY	AMP	REVISED	10/05/01	BY	AMP
DRAWN BY		DESIGNED BY	108-1471	CUSTOMER DRAWING					
CHECKED BY		APPROVED BY		CUSTOMER DRAWING					
DATE		10/07/99	DATE	10/07/99	BY	AMP	REVISED	10/07/99	BY
PART NO		5787191	CUSTOMER DRAWING						