


(b) STRIPPING DIMENSIONS



NOTES:

1. MATERIAL: COPPER ALLOY
2. PLATING: SEE TABLE
- (b) 3. CRIMPING: USE CRIMP TOOL 360X10329X WITH TOOL INSERT 360X20039X
SELECTOR SETTINGS: 7 FOR AWG 20
6 FOR AWG 22
5 FOR AWG 24

Plating	Part no.
min. 30µ" HARD GOLD over min. 50µ" NICKEL	132C15019X
min. 50µ" HARD GOLD over min. 50µ" NICKEL	132J15019X

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

finish: SEE NOTES				tolerance ISO 2768-m		dim. in mm		scale: 10:1	
				date		name		material: SEE NOTES	
				drawn 30.01.02		Parei		SIGNAL CRIMP CONTACT SOCKET CONTACT Wire Size 20-24	
				appd. 30.01.02		Mickenbecker			
6 x d		Ä 2532		12.07.06		HS		dwg no: Inventor 10 (d) DIN-A3 sh: 1 part no: SEE TABLE	
2 x c		Ä 2193		21.03.05		Lehmen d-old			
2 x b		Ä 2177		02.03.05		Lehmen			
a		Origin							
rev.		description		date		name			

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH. DO NOT ALTER CAD DRAWING BY HAND