



"AMP", PART NO. & DATE CODE, MARKED IN AREA INDICATED, ON FAR SIDE

- CONNECTOR ACCEPTS SIZE 20 DF PIN CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
  - CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.
- ▲ MOLDED PARTS: NYLON, FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, BLACK.
  - ▲ SHELLS: STEEL PER ASTM A109.
  - ▲ TIN OR TIN-LEAD PLATED OVER COPPER UNDERPLATE.
  - ▲ TIN PLATED OVER COPPER UNDERPLATE.

	STANDARD	▲	NO	.120	207464-7
	SMALL PACK	▲	YES	.120	207464-6
SUPERSEDED BY 207464-2	STANDARD	▲	YES	.154	207464-4
SUPERSEDED BY 207464-2	STANDARD	▲	NO	.154	207464-3
	STANDARD	▲	YES	.120	207464-2
SUPERSEDED BY 207464-7	STANDARD	▲	NO	.120	207464-1
	PACKAGING TYPE		SHELL FINISH	GROUNDING INDENTS	A
					PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNED BY: S. WELDON	DATE: 7-19-85
CHECKED BY: J. GERACE	DATE: 7-29-85
APPROVED BY: [Signature]	DATE: [Blank]
PRODUCT SPEC: [Blank]	APPLICATION SPEC: [Blank]
WEIGHT: [Blank]	SIZE: A2
CAGE CODE: 00779	DRAWING NO: C-207464
CUSTOMER DRAWING	SCALE: 4:1

TE Connectivity  
PLUG CONNECTOR, SIZE 3, 25 POSITION, AMPLIMITE™ HDP

RESTRICTED TO: [Blank]

SCALE: 4:1 SHEET: 1 of 1 REV: H