



- THIS RCPT. IS DESIGN TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
  - MAX WIRE INSUL TO BE USED WITH THIS RCPT IS .054 DIA.
  - METAL RETENTION CLIPS AREA INCLUDED IN INSERTS.
  - THIS RCPT WILL ACCEPT SIZE 22 SOCKET CONTACT M 39029/57-354 OR ANY HDU-22 CONTACT.
- △ TYCO PART NO. STAMPED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS.  
 △ UL/CSA DESIGNATION STAMPED ON SHELL.  
 △ FINISH: PLATED BRIGHT TIN .000400 MIN THK PER ASTM-B-545 OVER COPPER PLATE .000050 MIN THK PER MIL-C-14550.

204500-4	-	-	△	STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TP3013030 PER ASTM D5927	204500-4
-	-	-	CADMIUM PER QQ-P-416	STEEL, CLASS G	PHENOLIC GROUNDING COILS, BRASS	204500-3
-	-	-	CADMIUM PER QQ-P-416	BRASS	DUAL IN PATH PLATE SOLID, BRASS	204500-2
204512-2	M24308/2-286F	M24308/2-11F	△	STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TP3013030 PER ASTM D5927	204500-1
TYCO P/N MARKED ON CONNECTOR	MILITARY P/N ON PACKAGE	MILITARY P/N ON CONNECTOR	SHELL FINISH	SHELL MATERIAL	INSERT MATERIAL	PART NUMBER

SUPSD BY 204500-1  
 SUPSD BY 206499-4

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 11-18-93  
 DESIGNED BY: J. MILLER DATE: 11-18-93  
 DRAWN BY: J. MILLER DATE: 11-18-93  
 CHECKED BY: DATE: 11-18-93  
 APPROVED BY: DATE: 11-18-93  
 CUSTOMER DRAWING: DATE: 11-18-93  
 SIZE: 1.15 POS. SERIES 90  
 DRAWING NO: 100779  
 PART NO: 204500  
 REV: 4.1  
 SHEET: 1 OF 1