



- ⚠ RCPT ACCEPTS SIZE 20 DF SOCKET CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.
- 2. ALL PARTS SHIPPED UNASSEMBLED.
- ⚠ 3 FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.
- ⚠ 4 FLAME RETARDANT 94V-0 RATED GLASS FILLED, NYLON OR POLYESTER, BLACK.
- ⚠ 5 STEEL PER ASTM A109.
- ⚠ 6 .000200 MIN TIN PLATE OVER .000100 MIN COPPER UNDERPLATE.
- ⚠ 7 ZINC PHOSPHATE COATING, BLACK.
- ⚠ 8 COMPONENTS INDIVIDUALLY BULK PACKED.

⚠	W/LOGO	1658660-1
PACKAGING	REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	31.JUL.03	BY	J. BELTZEL
DRAWN BY		DATE	31.JUL.03	BY	S. BOLASH
CHECKED BY		DATE	31.JUL.03	BY	M. MALONEY
DIMENSIONS		INCH		PRODUCT SPEC	108-40030
APPROVALS		APPLICATION SPEC	114-40030	DATE	00779
MATERIAL INSERT		FINISH		SCALE	2:1
SHELLS & SHIELDS		FINISH		SHEET	1 OF 1
JACKSCREWS: ZINC ALLOY		FINISH		REV	0

AMP AMP Incorporated
Harrisburg, PA 17105-3608

BULK KIT, RCPT, SHIELDING ENCLOSURE, SIZE 4, 37 POSN, AMPLIMITE™ HDP-20