



PLUG CONNECTOR
 INSERTS: BLACK GLASS-FILLED NYLON, 94V-0 RATED.
 SHELLS: STEEL PER ASTM A109, PLATED, .000200 MIN TIN OVER .000100 MIN COPPER UNDERPLATE.



- 1. PLUG ACCEPTS SIZE 20 PIN CONTACTS (CONTACTS MUST BE ORDERED SEPARATELY).
- 2. ALL PARTS SHIPPED UNASSEMBLED, EACH PART INDIVIDUALLY BULK PACKED.
- 3. SHIELDS: MATERIAL-.020 THICK STEEL, PER ASTM A109, PLATED .000200 MIN TIN OVER .000100 MIN COPPER UNDERPLATE.
- 4. RAISED CAVITY IDENTIFICATION AND AMP TRADEMARK.

1658648-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE: 30.JUL.03	AMP Incorporated Harrisburg, PA 17105-3608	
DRAWN BY: J. BELTZEL		DATE: 30.JUL.03		
CHECKED BY: S. BOLASH		DATE: 30.JUL.03		
DESIGNED BY: M. WALSHLEY		DATE: 30.JUL.03	KIT, PLUG, SHIELDING HARDWARE, SIZE 3, 25 POSITION, AMPLIMITE™ HDP-20	
PARTIAL: SEE CALL OUT & NOTE		PRODUCT SPEC: 108-40030	DATE: 07.29.03	SCALE: 2:1
FINISH: SEE CALL OUT & NOTE		APPLICATION SPEC: 114-40030	CAGE CODE: 1658648	SHEET: 1 OF 1
		HEIGHT: -	REV: 0	
		CUSTOMER DRAWINGS		