



- 1. CONNECTOR ACCEPTS 22 DF SOCKET CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
- ⚠️ FLAME RETARDANT 94V-0 RATED GLASS FILLED NYLON, COLOR: BLACK.
- ⚠️ CARBON STEEL.
- ⚠️ .000200 MIN. TIN PLATE OVER .000100 MIN. COPPER UNDERPLATE.

1658685-1  
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT		DWG: L. BAUM 02JAN04 CHK: S. BOLASH 02JAN04 DES: M. WALMSLEY 02JAN04 DATE: 10B-1268 APPLICATION SPEC: 114-10001 HEIGHT: -	AMP Incorporated Harrisburg, PA 17105-3608 RECEPTACLE ASSEMBLY, SIZE 5, 7B POSN. HDP-22, AMPLIMITE®	TITLE: CASE CODE DRAWING NO: A200779 PART NUMBER: 1658685 SCALE: 3:1 SHEET 1 OF 1 REV 0	RESTRICTED TO: -
DIMENSIONS: INCH DIMENSIONS: DECIMALS: 4 DIMENSIONS: FRACTIONS: 16 DIMENSIONS: ANGLES: 12	MATERIAL: MOLDED PARTS: ⚠️ SHELLS: ⚠️	FINISH: SHELLS: ⚠️	CUSTOMER DRAWINGS		