



- THIS RECEPTACLE WILL MATE WITH ANY PLUG CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18274-1.
  - MAXIMUM WIRE INSULATION USED WITH THIS RCPT. IS .072 DIA. MAX.
  - Be-Cu RETENTION CLIPS ARE INCLUDED IN INSERTS.
- △ CUSTOMER PART NUMBER MAY BE SPLIT BETWEEN FRONT AND REAR SHELLS, SAME SIDE. FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE, NEAR SIDE REFERS TO NARROW SIDE OF KEYSTONE.
- △ UL/CSA DESIGNATION STAMPED IN THIS AREA.
- △ THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.
- △ RESTRICTED TO CAE ELECTRONICS ONLY.
- △ CONNECTOR SUPPLIED WITH CONTACTS, AMP PART NUMBER 206793-1; (NOT INSTALLED).

△	.120	570513-2	206799-7	206799-7
△	.120	LMSC 1621480-002	206799-6	206799-6
△	.120	LMSC 1621480-002	206799-5	206799-5
△	.120	311P409-2S-B-12	206799-2	206799-4
	.154		206799-3	206799-3
	.120	311P409-2S-B-12	206799-2	206799-2
	.154	311P409-2S-B-15	206799-1	206799-1
REMARKS	DIA A	MARKED CUSTOMER P/N	MARKED AMP P/N	AMP P/N

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 12-18-88 BY: CLOUSER  
 12-18-88  
 CONTROL  
 Tyco Electronics Corporation  
 Harrisburg, PA 17105-2608

RECEPTACLE FOR SOCKET CONTACTS  
 HI-DENSITY HDW CONNECTOR  
 SIZE #2 (15 POS) NON-MAGNETIC

SIZE: 100779 (G)=206799  
 CUSTOMER DRAWING  
 SHEET 4:1 OF 1