



- THIS PLUG WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18274-2.
 - MAXIMUM WIRE INSULATION USED WITH THIS PLUG IS .054 DIA.
 - Be-Cu RETENTION CLIPS ARE INCLUDED IN INSERTS.
- ▲ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
 - ▲ INSPECTION REQUIREMENTS PER R4383.
 - ▲ CONNECTOR SUPPLIED WITH 29 CONTACTS, AMP PART NUMBER 204370-8.
 - ▲ CUSTOMER PART NUMBER MAY BE SPLIT BETWEEN FRONT AND REAR SHELLS, SAME SIDE.
 - ▲ 36 CONTACTS, AMP PART NUMBER 204370-8, SUPPLIED WITH EACH CONNECTOR.
 - ▲ CONNECTOR LOADED WITH POSTED CONTACTS, INSPECTION REQUIREMENTS PER GENERAL ELECTRIC DOCUMENT 20625720.
 - ▲ RESTRICTED TO CAE ELECTRONICS ONLY.
 - ▲ THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.
 - ▲ CONNECTOR LOADED WITH POSTED CONTACTS.
 - ▲ PRELIMINARY PART NO, NOT RELEASED FOR PRODUCTION
 - ▲ CONNECTORS LOADED WITH POSTED CONTACTS, INSPECTION REQUIREMENTS PER LOCKHEED-MARTIN DOCUMENT 20131204

.150±.025	▲▲▲	.120	20131204P2026P	1-206500-3	1-206500-3
		.120	570566-8	1-206500-2	1-206500-2
.175±.025	▲▲▲	.120	-	1-206500-1	1-206500-1
		.120	311P407-2P-B-12	206500-4	1-206500-0
.150±.025	▲▲▲	.120	2025720P2026P	206500-9	206500-9
		.120	326113-9	206500-8	206500-8
		.154	1622251-004	206500-7	206500-7
		.120	R4383P26P	206500-6	206500-6
		.120	R4383P26P-2	206500-5	206500-5
		.120	311P407-2P-B-12	206500-4	206500-4
		.154	-	206500-3	206500-3
		.120	R9259P26P	206500-2	206500-2
		.154	311P407-2P-B-15	206500-1	206500-1

DIM B	REMARKS	DIA A	MARKED CUSTOMER P/N	MARKED AMP P/N	AMP PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

CAE ELECTRONICS CORPORATION
 17100-3608
 Harrisburg, PA 17100-3608

PLUG FOR SOCKET CONTACTS
 H-DENSITY 0, 26 POSN, SIZE 2
 NONMAGNETIC.

DATE: 00779
 DRAWING NO: 206500
 CUSTOMER DRAWING