



DO NOT SCALE
DIMENSIONS IN mm

METRIC

THIRD ANGLE PROJECTION

- NOTES:**
- 1 THIS PLUG ACCEPTS SIZE 20 PIN CONTACTS
 - 2 MAXIMUM WIRE INSULATION RECOMMENDED FOR USE WITH THIS PLUG IS 1,73 DIA. MAX..
 - 3 RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
 - 4 CONTACTS SHOWN FOR ILLUSTRATION ONLY, NO PART OF CONNECTOR PACKAGE, MUST BE ORDERED SEPARATELY.
 - 5 FOLLOWING INSERTION/REMOVAL TOOLS ARE RECOMMENDED FOR USE WITH THESE CONNECTORS:

32-28AWG/28-24AWG CONTACTS	24-20AWG CONTACTS
91067-3 INSERTION/REMOVAL	91067-2 INSERTION/REMOVAL
726363-1 INSERTION ONLY	726364-1 INSERTION ONLY
	726364-1 REMOVAL ONLY

FRONT SHELL STEEL, BRIGHT TINPLATED WITH 2x5 GROUNDING FINGERS AT 7,6 PITCH.

REAR SHELL, STEEL BRIGHT TINPLATED.

AMP DATE CODE AMP PARTNO. INK STAMPED

INSERTS: NYLON GLASS-FILLED SELF-EXTINGUISHING COLOR: BLACK

SEE DETAIL X

DETAIL X

(TAB-THICKNESS : 0,4)

SEE DRAWING	SEE DRAWING	188289-1
FINISH	MATERIAL	PARTNUMBER
-	-	-
CUSTOMER DRAWING		FOR REFERENCE ONLY WILL NOT BE UPDATED
© COPYRIGHT 19- BY AMP HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION		
AMP		AMP HOLLAND B.V. 's-Hertogenbosch, The Netherlands.
NAME HDP-20 PLUG CONNECTOR, SIZE 5, (50 POSITION) WITH SOLDER TABS		
LTR.	REVISION RECORD	DR. CHK. DATE
B	EH-0511-94	R.I.V. R.F. OSMARSB
DR. : L.V.D.HEIJDEN	CHK. : C.V.TILBURG	APP. : L.V.SOEST
DATE: 30.06.87	DATE: 07-07-87	DATE: 28-07-87
DWG.No. C-215714		REV.LTR. SHEET B 1 OF 1