



1. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
 2. MAX WIRE INSULATION TO BE USED WITH THIS PLUG IS .054 DIA.
 3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS.
 4. PACKAGE STAMPED M 24308/4-264F.
 5. THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 39029/58-360 OR ANY TE CONNECTIVITY HDO-22 PIN CONTACT.
- ▲ TE CONNECTIVITY PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS.
 ▲ UL / CSA DESIGNATION STAMPED ON SHELL.
 ▲ PART NO. 204501-4, -5 & 5--4 HAS GROUNDING INDENTS ON FRONT SHELL. (NOT SHOWN)
 ▲ FINISH: BRIGHT TIN .000400-.000550 THK PER ASTM-B-545 OVER COPPER .000050 MIN THK PER AMS2418.
 ▲ M24308/4-11F MARKED ON FAR SIDE. 204513-2 MARKED ON NEAR SIDE.
 ▲ CONTACTS ARE NOT INCLUDED IN THIS ASSEMBLY. MUST BE ORDERED SEPARATELY.
 ▲ SAME AS 204501-5 EXCEPT WITHOUT GROUNDING INDENTS.

▲▲	BRIGHT TIN	STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) PER GST-40F COLOR: BLACK	5-204501-4
▲▲		STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TPES013030 PER ASTM D5927	204501-6
▲▲		STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TPES013030 PER ASTM D5927	204501-5
▲▲	BRIGHT TIN	STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TPES013030 PER ASTM D5927	204501-4
SUPSD BY 204501-1		STEEL, CLASS G	PHENOLIC COLOR: BLACK	204501-3
SUPSD BY 206498-4		STEEL, CLASS G	GLASS FIBER REINF. FLAME RETARDANT POLYESTER COLOR: BLUE	204501-2
▲▲		STEEL, CLASS G	POLYPHENYLENE SULFIDE (PPS) GST-40F PER MIL-M-24519 OR GLASS FILLED POLYESTER TPES013030 PER ASTM D5927	204501-1
REMARKS	SHELL FINISH	SHELL MAT'L	INSERT MAT'L	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. (P. THOMAS) (SUPERVISOR)

DESIGNED BY: J. MARSEY
 DRAWN BY: J. MARSEY
 CHECKED BY: J. MARSEY
 APPROVED BY: J. MARSEY

TE Connectivity
 PLUG ASSY/PLUMTE, 15 POSN
 SIZE 1, SERIES 90

DATE: 10/07/79
 DRAWING NO: 204501
 CUSTOMER DRAWING