



- THIS RECEPTACLE WILL MATE WITH ANY 17C2, SIZE 3 PLUG IN AMPLIMITE SERIES.
  - MAXIMUM WIRE INSULATION TO BE USED WITH THIS RECEPTACLE IS .068.
  - THIS CONNECTOR ACCEPTS (2) POWER 8, OR COAX SOCKET CONTACTS IN POSITIONS A1 THRU A2, PURCHASED SEPARATELY.
  - THIS CONNECTOR ACCEPTS SIZE 20 SOCKET SIGNAL CONTACTS IN POSITIONS 1 THRU 15, PURCHASED SEPARATELY.
- △ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
  - △ STEEL PER ASTM-A-109.
  - △ BRASS PER MIL-C-50 AND ASTM-B-36 UNS NO. C26000.
  - △ FINISH: CADMIUM PLATED PER QQ-P-416.
  - △ GOLD PLATED PER MIL-G-45204 TYPE II, GRADE C, CLASS 1 OVER COPPER PER MIL-C-14550, CLASS IV.
  - △ FINISH: TIN PER ASTM-B-545 .000200 MIN THK OVER COPPER PER AMS2418 .000100-.000200 THK.
  - △ FINISH: TIN PER ASTM-B-545 .000400 MIN THK OVER COPPER PER AMS2418 .000050 MIN THK.
  - △ FINISH: TIN PER ASTM-B-545 .000200 MIN THK OVER COPPER PER AMS2418 .000100-.000200 THK.
  - △ FINISH: ZINC PLATE PER ASTM-B-633 .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (C-3+).

PRELIMINARY NOT RELEASED FOR PRODUCTION

△△	.120	-	5-212510-1
△△	.120	-	5-212510-4
△△	.120	-	212510-5
△△	.120	-	212510-4
△△	.154	311P405-13S-B-15	212510-3
△△	.120	311P405-13S-B-12	212510-2
△△	.120	-	212510-1
REMARKS	8A	GSFC P/N	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	BY	APP'D
REVISIONS:		DATE	BY	APP'D
REV	DESCRIPTION	DATE	BY	APP'D
1	RECEPTACLE ASSEMBLY			
REVISIONS:		DATE	BY	APP'D
1	RECEPTACLE ASSEMBLY			
REVISIONS:		DATE	BY	APP'D
1	RECEPTACLE ASSEMBLY			
REVISIONS:		DATE	BY	APP'D
1	RECEPTACLE ASSEMBLY			
REVISIONS:		DATE	BY	APP'D
1	RECEPTACLE ASSEMBLY			